



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Waterproof ExStik[®] pH Meter



Flat surface electrode design

Provides fast and easy on-the-spot pH measurements

Features:

- Flat Surface Electrode measures pH in liquids, semi-solids, and solids. No more electrode breakage or clogged junctions.
- RENEW indicator tells you when it's time to replace your electrode which eliminates guesswork
- CAL alert tells you it's time to recalibrate. Ensures accuracy.
- Memory records and recalls 15 sequentially tagged readings allowing detection of changes over time
- Analog bargraph displayed on LCD
- 1, 2 or 3 point calibration automatically recognizes buffer solutions. Order pH buffers separately.
- Automatic Temperature Compensation
- Simultaneous display of pH and Temperature
- Display indicates when the reading is stabilized
- Data Hold, Auto power off and low battery indication
- Waterproof design (IP57) floats in water and protects the meter in wet environment
- Interchangeable probes available for Chlorine & ORP
- Optional weighted base (EX006) holds plastic cup and ExStik[®] meter
- Complete with flat surface pH electrode, protective sensor cap, sample cup with cap, four 3V CR-2032 button batteries, and 48" (1.2m) neckstrap. **Order pH buffers separately**



Flat Surface Electrodes work in liquids, semi-solids and solids

Ordering Information:

- PH100Waterproof ExStik[®] pH Meter
 PH105Spare pH ExStik[®] Electrode Module
 EX006Weighted base with 5 solution cups
 PH103Tripak buffers (6ea - 4, 7, 10pH & 2 Rinse solutions)
 EX007Spare sample solution cups (24pk)
 RE305Flat Surface ORP electrode module
 CL205Flat Surface Chlorine electrode module
 PH115Flat Surface Refillable pH electrode module
 CA895Carrying Case, Small with Belt Loop

Specifications	
pH	0.00 to 14.00pH
Temperature	23 to 194°F (-5 to 90°C)
Resolution	0.01pH, 0.1°
Accuracy	±0.01pH, ±1.8°F/±1°C
Power	four 3V CR3032 button batteries
Dimensions	1.4 x 6.8 x 1.6" (35.6 x 172.7 x 40.6mm)
Weight	3.8oz (110g)

