imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Part

Number

PM125SH-100M

PM125SH-120M

PM125SH-150M

PM125SH-180M

PM125SH-220M

PM125SH-270M


PM125SH-330M


PM125SH-390M

PM125SH-470M

Special Features

- High current capacity
- Magnetic shielded for low radiation
- Ferrite bobbin core
- Low core loss for high frequency power application
- Compact size
- Large terminal surface for good PCB bonding
- Operating temperature -30 to +100°C
- Current to cause maximum 25% of inductance drop, or 40°C temperature rise
- Tape & reel packaged 500/reel





Dim: mm Tol: -/+0.3

Pad Layout

1 68 1 82 1 100 1 120 1 150 1 180 1 220 1 270	0.12 0.14 0.16 0.17 0.23 0.29 0.40	1.5 1.4 1.3 1.1 1.0 0.90	
1 100 1 120 1 150 1 180 1 220	0.16 0.17 0.23 0.29	1.3 1.1 1.0 0.90	
1 120 1 150 1 180 1 220	0.17 0.23 0.29	1.1 1.0 0.90	_
1 150 1 180 1 220	0.23	1.0 0.90	_
1 180 1 220	0.29	0.90	
1 220			
	0.40	0 00	
1 270		0.80	
210	0.46	0.75	
1 330	0.51	0.68	
1 390	0.69	0.65	
1 470	0.77	0.58	
1 560	0.86	0.54	
1 680	1.20	0.48	
1 820	1.34	0.43	
1 1000	1.53	0.40	
	1 470 1 560 1 680 1 820	470 0.77 560 0.86 680 1.20 820 1.34	470 0.77 0.58 1 560 0.86 0.54 1 680 1.20 0.48 1 820 1.34 0.43

PM125SH Series

DCR

(Ω)

Max.

0.025

0.027

0.030

0.034

0.036

0.051

0.057

0.068

0.075

I, DC

(A)

4.0

3.5

3.3

3.0

2.8

2.3

2.1

2.0

1.8

L (uH) ±20%

@ 1KHz

10

12

15

18

22

27

33

39

47



306 E. Alondra Blvd., Gardena, CA 90247-1059 • (310) 515-1720 • FAX (310) 515-1962 www.jwmiller.com