

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









U Contact


Data Sheet PM20CxxVBNN

Page 1/4 P/N PM20CxxVBNN xx=number of poles 2017/05/05

Illustration









Product specification

- pin header, SMT solderable
- centerline 2.00 mm, direction of connection vertical 0°
- color black
- Tape & Reel packaging
- · single row

Plus de documentation technique à télécharger sur www.metz-connect.com







Page 2/4
P/N
PM20CxxVBNN
xx=number of poles
2017/05/05

Data Sheet PM20CxxVBNN

	-	
Technical Data		
General Data		
min. number of poles	2	
max. number of poles	40	
Approvals		
Rated current	1 A	
Material		
insulating material	PE-HT	
Glow-Wire Flammability GWFI	-	
Glow-Wire Flammability GWIT	•	
contact pin material	CuZn	
contact pin surface	Ni + Au Flash	
Climatic properties		
upper limit temperature	105 °C	
lower limit temperature	-40 °C	
General		
solderability	Acc. to IPC/JEDEC J-STD-020D-MSL 1	

ISO 2768 -mH

Tolerance








Page 3/4 P/N PM20CxxVBNN xx=number of poles 2017/05/05


Data Sheet PM20CxxVBNN

Illustration









L=(pole size - 1) x centerline + 2.0 [0.079]





Page 4/4 P/N PM20CxxVBNN xx=number of poles 2017/05/05

Data Sheet PM20CxxVBNN

PCB Layout

