



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





PMCM650CUNE

20 V, Common Drain N-channel Trench MOSFET

Rev. 1.0 — 8 November 2017

Product data sheet

1 Product profile

1.1 General description

N-channel enhancement mode common-drain dual Field-Effect Transistor (FET) in a 6 bumps Wafer Level Chip-Size Package (WLCSP) using Trench MOSFET technology.

1.2 Features and benefits

- Common-drain type for bi-directional current flow
- Low threshold voltage
- Ultra small package: 0.98 × 1.48 × 0.35 mm
- Trench MOSFET technology
- ElectroStatic Discharge (ESD) protection > 2 kV HBM

1.3 Applications

- Loadswitch
- Battery Protection
- Battery Management

1.4 Quick reference data



Table 1. Quick reference data

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{SS}	source-source voltage	$T_j = 25\text{ °C}$	-	-	20	V
V_{GS}	gate-source voltage		-8	-	8	V
I_S	source current	$T_{amb} = 25\text{ °C}; V_{GS} = 4.5\text{ V}; t \leq 5\text{ s}$ [1]	-	-	5.3	A
Static characteristics						
R_{SSon}	source-source on-state resistance	$V_{GS} = 4.5\text{ V}; I_S = 3\text{ A}; T_j = 25\text{ °C}$	-	40	52	mΩ

[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and mounting pad for drain 6 cm².

2 Pinning information

Table 2. Pinning

Pin	Symbol	Description	Simplified outline	Graphic symbol
A1	G1	gate 1	 <p>Transparent top view</p>	
A2	S1	source 1		
B1	S2	source 2		
B2	S1	source 1		
C1	S2	source 2		
C2	G2	gate 2		

3 Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
PMCM650CUNE	WLCSP6	wafer level chip-size package; 6 bumps (3 x 2)	WLCSP6_3-2

4 Marking

Table 4. Marking codes

Type number	Marking code
PMCM650CUNE	AH

5 Limiting values


Table 5. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions		Min	Max	Unit
V_{SS}	source-source voltage	$T_j = 25\text{ °C}$		-	20	V
V_{GS}	gate-source voltage	$T_j = 25\text{ °C}$		-8	8	V
I_S	source current	$T_{amb} = 25\text{ °C}; V_{GS} = 4.5\text{ V}; t \leq 5\text{ s}$	[1]	-	5.3	A
		$T_{amb} = 25\text{ °C}; V_{GS} = 4.5\text{ V}$	[1]	-	4.1	A
		$T_{amb} = 100\text{ °C}; V_{GS} = 4.5\text{ V}$	[1]	-	2.6	A
I_{SM}	peak source current	$T_{amb} = 25\text{ °C}$; single pulse; $t_p \leq 10\text{ }\mu\text{s}$		-	16	A
P_{tot}	total power dissipation	$T_{amb} = 25\text{ °C}$	[2]	-	556	mW
		$T_{amb} = 25\text{ °C}$	[1]	-	1300	mW
		$T_{sp} = 25\text{ °C}$		-	12500	mW
T_j	junction temperature			-55	150	°C
T_{amb}	ambient temperature			-55	150	°C
T_{stg}	storage temperature			-65	150	°C
Source-Forward diode						
I_{FS}	source-forward current	$T_{amb} = 25\text{ °C}$	[1]	-	1.2	A


[1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper, tin-plated and mounting pad for drain 6 cm^2 .

[2] Device mounted on an FR4 PCB, single-sided copper; tin-plated and standard footprint.



$$P_{der} = \frac{P_{tot}}{P_{tot}(25\text{ }^\circ\text{C})} \times 100\%$$

Figure 1. Normalized total power dissipation as a function of junction temperature



$$I_{der} = \frac{I_{SS}}{I_{SS}(25\text{ }^\circ\text{C})} \times 100\%$$

Figure 2. Normalized continuous source-source current as a function of junction temperature




Figure 3. Safe operating area; junction to ambient; continuous and peak source currents as a function of source-source voltage

6 Thermal characteristics

Table 6. Thermal characteristics

Symbol	Parameter	Conditions		Min	Typ	Max	Unit
$R_{th(j-a)}$	thermal resistance from junction to ambient	in free air	[1]	-	180	225	K/W
			[2]	-	65	85	K/W
			[3]	-	75	95	K/W
		in free air; $t \leq 5$ s	[3]	-	45	55	K/W
$R_{th(j-sp)}$	thermal resistance from junction to solder point			-	5	10	K/W

- [1] Device mounted on an FR4 Printed-Circuit Board (PCB), single-sided copper; tin-plated and standard footprint.
- [2] Device mounted on an FR4 PCB, single-sided copper, tin-plated and mounting pad for drain, 4 layer, 1 cm².
- [3] Device mounted on an FR4 PCB, single-sided copper, tin-plated and mounting pad for drain 6 cm².






Figure 4. Transient thermal impedance from junction to ambient as a function of pulse duration; typical values



7 Characteristics


Table 7. Characteristics
 $T_j = 25\text{ °C}$ unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static characteristic						
$V_{(BR)SS}$	source-source breakdown voltage	$I_S = 250\ \mu\text{A}$; $V_{GS} = 0\ \text{V}$;	20	-	-	V
V_{GSth}	gate-source threshold voltage	$I_D = 250\ \mu\text{A}$; $V_{SS} = V_{GS}$	0.4	0.7	0.9	V
I_{SSS}	source leakage current	$V_{GS} = 0\ \text{V}$; $V_{SS} = 20\ \text{V}$	-	-	1	μA
I_{GSS}	gate leakage current	$V_{GS} = 8\ \text{V}$; $V_{SS} = 0\ \text{V}$	-	-	10	μA
		$V_{GS} = -8\ \text{V}$; $V_{SS} = 0\ \text{V}$	-	-	-10	μA
		$V_{GS} = 4.5\ \text{V}$; $V_{SS} = 0\ \text{V}$	-	-	1	μA
		$V_{GS} = -4.5\ \text{V}$; $V_{SS} = 0\ \text{V}$	-	-	-1	μA
		$V_{GS} = 2.5\ \text{V}$; $V_{SS} = 0\ \text{V}$	-	-	200	nA
		$V_{GS} = -2.5\ \text{V}$; $V_{SS} = 0\ \text{V}$	-	-	-200	nA
R_{SSon}	source-source on-state resistance	$V_{GS} = 4.5\ \text{V}$; $I_S = 3\ \text{A}$; $T_j = 25\text{ °C}$	-	40	52	m Ω
		$V_{GS} = 4.5\ \text{V}$; $I_S = 3\ \text{A}$; $T_j = 150\text{ °C}$	-	55	71	m Ω
		$V_{GS} = 2.5\ \text{V}$; $I_S = 2\ \text{A}$; $T_j = 25\text{ °C}$	-	50	62	m Ω
		$V_{GS} = 1.8\ \text{V}$; $I_S = 1\ \text{A}$; $T_j = 25\text{ °C}$	-	63	95	m Ω
g_{fs}	forward transconductance	$V_{GS} = 4.5\ \text{V}$; $I_S = 3\ \text{A}$	-	22	-	S
R_G	gate resistance	$f = 1\ \text{MHz}$	-	6.6	-	Ω
Dynamic characteristics						
$Q_{G(tot)}$	total gate charge	$V_{SS} = 10\ \text{V}$; $I_S = 3\ \text{A}$; $V_{GS} = 4.5\ \text{V}$	-	9	13	nC
Q_{GS}	gate-source charge		-	0.7	-	nC
Q_{GD}	gate-drain charge		-	2.9	-	nC
C_{iss}	input capacitance	$V_{SS} = 10\ \text{V}$; $f = 1\ \text{MHz}$; $V_{GS} = 0\ \text{V}$	-	480	-	pF
C_{oss}	output capacitance		-	96	-	pF
C_{rss}	reverse transfer capacitance		-	96	-	pF
$t_{d(on)}$	turn-on delay time		$V_{SS} = 10\ \text{V}$; $I_S = 3\ \text{A}$; $V_{GS} = 4.5\ \text{V}$; $R_{G(ext)} = 6\ \Omega$	-	6	-
t_r	rise time	-		20	-	ns
$t_{d(off)}$	turn-off delay time	-		39	-	ns
t_f	fall time	-		15	-	ns
Source-Forward diode						
V_{FS}	source-forward voltage	$V_{G1S1} = 0\ \text{V}$; $V_{G2S2} = 4.5\ \text{V}$; $I_S = 1.2\ \text{A}$	-	0.7	1.2	V




$T_j = 25\text{ }^\circ\text{C}$

Figure 6. Output characteristics: source current as a function of source-source voltage; typical values




$V_{SS} = 5\text{ V}; T_j = 25\text{ }^\circ\text{C}$

Figure 7. Sub-threshold source current as a function of gate-source voltage




$T_j = 25\text{ }^\circ\text{C}$

Figure 8. Source-source on-state resistance as a function of source current; typical values




$I_S = 3\text{ A}$

Figure 9. Source-source on-state resistance as a function of gate-source voltage; typical values




$$V_{SS} > I_S \times R_{SSon}$$

Figure 10. Transfer characteristics: drain current as a function of gate-source voltage; typical values




$$a = \frac{R_{SSon}}{R_{SSon(25\text{ °C})}} \times 100\%$$

Figure 11. Normalized source-source on-state resistance as a function of junction temperature; typical values




$$I_S = 250 \mu\text{A}; V_{SS} = V_{GS}$$

Figure 12. Gate-source threshold voltage as a function of junction temperature



$$f = 1 \text{ MHz}; V_{GS} = 0 \text{ V}$$

Figure 13. Input, output and reverse transfer capacitances as a function of source-source voltage; typical values



$V_{SS} = 10\text{ V}$; $I_S = 3\text{ A}$; $T_{amb} = 25\text{ }^\circ\text{C}$

Figure 14. Gate-source voltage as a function of gate charge; typical values





Figure 15. Common Drain MOSFET gate charge definitions



$V_{G1S1} = 0\text{ V}$; $V_{G2S2} = 4.5\text{ V}$

Figure 16. Source current as a function of source-source voltage; typical values

8 Test information





Figure 17. Duty cycle definition



aaa-027255

9 Package outline





Figure 19. Package outline WLCSP6_3-2

10 Soldering



11 Revision history

Table 8. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
PMCM650CUNE v.1	20171108	Product data sheet	-	-

12 Legal information

12.1 Data sheet status

Document status ^{[1][2]}	Product status ^[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nexperia.com>.

12.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

12.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia. In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory. Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the Terms and conditions of commercial sale of Nexperia.

Right to make changes — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — Nexperia products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical

systems or equipment, nor in applications where failure or malfunction of an Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification. Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products. Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nexperia.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific Nexperia product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Nexperia accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications. In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Nexperia's warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Nexperia's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Nexperia for any liability, damages or failed product claims resulting from customer

design and use of the product for automotive applications beyond Nexperia's standard warranty and Nexperia's product specifications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

12.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

Tables

Tab. 1.	Quick reference data	1	Tab. 5.	Limiting values	3
Tab. 2.	Pinning	2	Tab. 6.	Thermal characteristics	5
Tab. 3.	Ordering information	2	Tab. 7.	Characteristics	7
Tab. 4.	Marking codes	2	Tab. 8.	Revision history	14

Figures

Fig. 1.	Normalized total power dissipation as a function of junction temperature	4	Fig. 10.	Transfer characteristics: drain current as a function of gate-source voltage; typical values	9
Fig. 2.	Normalized continuous source-source current as a function of junction temperature	4	Fig. 11.	Normalized source-source on-state resistance as a function of junction temperature; typical values	9
Fig. 3.	Safe operating area; junction to ambient; continuous and peak source currents as a function of source-source voltage	4	Fig. 12.	Gate-source threshold voltage as a function of junction temperature	9
Fig. 4.	Transient thermal impedance from junction to ambient as a function of pulse duration; typical values	5	Fig. 13.	Input, output and reverse transfer capacitances as a function of source-source voltage; typical values	9
Fig. 5.	Transient thermal impedance from junction to ambient as a function of pulse duration; typical values	6	Fig. 14.	Gate-source voltage as a function of gate charge; typical values	10
Fig. 6.	Output characteristics: source current as a function of source-source voltage; typical values	8	Fig. 15.	Common Drain MOSFET gate charge definitions	10
Fig. 7.	Sub-threshold source current as a function of gate-source voltage	8	Fig. 16.	Source current as a function of source-source voltage; typical values	10
Fig. 8.	Source-source on-state resistance as a function of source current; typical values	8	Fig. 17.	Duty cycle definition	10
Fig. 9.	Source-source on-state resistance as a function of gate-source voltage; typical values	8	Fig. 18.	Test circuits	11
			Fig. 19.	Package outline WLCSP6_3-2	12
			Fig. 20.	Reflow soldering footprint WLCSP6	13

Contents

1	Product profile	1
1.1	General description	1
1.2	Features and benefits	1
1.3	Applications	1
1.4	Quick reference data	1
2	Pinning information	2
3	Ordering information	2
4	Marking	2
5	Limiting values	3
6	Thermal characteristics	5
7	Characteristics	7
8	Test information	10
9	Package outline	12
10	Soldering	13
11	Revision history	14
12	Legal information	15

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© Nexperia B.V. 2017.

All rights reserved.

For more information, please visit: <http://www.nexperia.com>

For sales office addresses, please send an email to: salesaddresses@nexperia.com

Date of release: 8 November 2017

Document identifier: PMCM650CUNE v.1