



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



# PMWD19UN

Dual µTrenchMOS™ ultra low level FET

Rev. 01 — 20 December 2002

Product data

## 1. Product profile

### 1.1 Description

Dual N-channel enhancement mode field-effect transistor in a plastic package using TrenchMOS™ technology.

Product availability:

PMWD19UN in SOT530-1 (TSSOP8).

### 1.2 Features

- Surface mounting package
- Very low threshold
- Low profile
- Fast switching.

### 1.3 Applications

- Portable appliances
- Battery management
- PCMCIA cards
- Load switching.

### 1.4 Quick reference data

- $V_{DS} \leq 30 \text{ V}$
- $P_{tot} \leq 2.3 \text{ W}$
- $I_D \leq 5.6 \text{ A}$
- $R_{DSon} \leq 23 \text{ m}\Omega$ .

## 2. Pinning information

Table 1: Pinning - SOT530-1, simplified outline and symbol

Pin	Description	Simplified outline	Symbol
1	drain1 (d1)		
2,3	source1 (s1)		
4	gate1 (g1)		
5	gate2 (g2)		
6,7	source2 (s2)		
8	drain2 (d2)		

The simplified outline shows a rectangular package with pins numbered 1 through 8. Pin 1 is at the bottom left, pin 8 is at the top left, pin 5 is at the top right, and pin 4 is at the bottom right. The symbol shows two back-to-back diodes with their cathodes connected to the source terminals (s1 and s2) and their anodes connected to the drain terminals (d1 and d2). The gate terminals (g1 and g2) are connected to the gates of the two transistors. The symbols are labeled with 'MSD901'.

Top view MBK885

SOT530-1




PHILIPS

### 3. Limiting values

**Table 2: Limiting values**


In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
$V_{DS}$	drain-source voltage (DC)	$25\text{ }^{\circ}\text{C} \leq T_j \leq 150\text{ }^{\circ}\text{C}$	-	30	V
$V_{DGR}$	drain-gate voltage	$25\text{ }^{\circ}\text{C} \leq T_j \leq 150\text{ }^{\circ}\text{C}; R_{GS} = 20\text{ k}\Omega$	-	30	V
$V_{GS}$	gate-source voltage		-	$\pm 10$	V
$I_D$	drain current (DC)	$T_{sp} = 25\text{ }^{\circ}\text{C}; V_{GS} = 4.5\text{ V}$ ; <a href="#">Figure 2 and 3</a>	-	5.6	A
		$T_{sp} = 100\text{ }^{\circ}\text{C}; V_{GS} = 4.5\text{ V}$ ; <a href="#">Figure 2</a>	-	3.4	A
$I_{DM}$	peak drain current	$T_{sp} = 25\text{ }^{\circ}\text{C}$ ; pulsed; $t_p \leq 10\text{ }\mu\text{s}$ ; <a href="#">Figure 3</a>	-	20	A
$P_{tot}$	total power dissipation	$T_{sp} = 25\text{ }^{\circ}\text{C}$ ; <a href="#">Figure 1</a>	-	2.3	W
$T_{stg}$	storage temperature		-55	+150	$^{\circ}\text{C}$
$T_j$	junction temperature		-55	+150	$^{\circ}\text{C}$
<b>Source-drain diode</b>					
$I_S$	source (diode forward) current (DC)	$T_{sp} = 25\text{ }^{\circ}\text{C}$	-	2	A
$I_{SM}$	peak source (diode forward) current	$T_{sp} = 25\text{ }^{\circ}\text{C}$ ; pulsed; $t_p \leq 10\text{ }\mu\text{s}$	-	7	A



$$P_{der} = \frac{P_{tot}}{P_{tot}(25^{\circ}C)} \times 100\%$$


**Fig 1.** Normalized total power dissipation as a function of solder point temperature.



$V_{GS} \geq 4.5$  V

$$I_{der} = \frac{I_D}{I_{D(25^{\circ}C)}} \times 100\%$$

**Fig 2.** Normalized continuous drain current as a function of solder point temperature.



$T_{sp} = 25^{\circ}C$ ;  $I_{DM}$  is single pulse


**Fig 3.** Safe operating area; continuous and peak drain currents as a function of drain-source voltage.

## 4. Thermal characteristics

**Table 3: Thermal characteristics**

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$R_{th(j-sp)}$	thermal resistance from junction to solder point	Figure 4	-	55	70	K/W
$R_{th(j-a)}$	thermal resistance from junction to ambient	minimum footprint; mounted on printed-circuit board	-	100	-	K/W

### 4.1 Transient thermal impedance




**Fig 4.** Transient thermal impedance from junction to solder point as a function of pulse duration.


## 5. Characteristics

**Table 4: Characteristics** $T_j = 25^\circ\text{C}$  unless otherwise specified

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
<b>Static characteristics</b>						
$V_{(\text{BR})\text{DSS}}$	drain-source breakdown voltage	$I_D = 250 \mu\text{A}; V_{GS} = 0 \text{ V}$				
		$T_j = 25^\circ\text{C}$	30	-	-	V
		$T_j = -55^\circ\text{C}$	27	-	-	V
$V_{GS(\text{th})}$	gate-source threshold voltage	$I_D = 1 \text{ mA}; V_{DS} = V_{GS}$ ; <b>Figure 9</b>	0.45	0.7	-	V
$I_{DSS}$	drain-source leakage current	$V_{DS} = 30 \text{ V}; V_{GS} = 0 \text{ V}$				
		$T_j = 25^\circ\text{C}$	-	-	1	$\mu\text{A}$
		$T_j = 150^\circ\text{C}$	-	-	100	$\mu\text{A}$
$I_{GSS}$	gate-source leakage current	$V_{GS} = \pm 10 \text{ V}; V_{DS} = 0 \text{ V}$	-	-	100	nA
$R_{DS\text{on}}$	drain-source on-state resistance	$V_{GS} = 4.5 \text{ V}; I_D = 3.5 \text{ A}$ ; <b>Figure 7 and 8</b>	-	-	-	$\text{m}\Omega$
		$T_j = 25^\circ\text{C}$	-	19	23	$\text{m}\Omega$
		$T_j = 150^\circ\text{C}$	-	32	39	$\text{m}\Omega$
		$V_{GS} = 1.8 \text{ V}; I_D = 3.5 \text{ A}$ ; <b>Figure 7</b>	-	25	35	$\text{m}\Omega$
		$V_{GS} = 2.5 \text{ V}; I_D = 3.5 \text{ A}$ ; <b>Figure 7</b>	-	21	26	$\text{m}\Omega$
<b>Dynamic characteristics</b>						
$Q_{g(\text{tot})}$	total gate charge	$I_D = 5 \text{ A}; V_{DD} = 16 \text{ V}; V_{GS} = 5 \text{ V}$ ; <b>Figure 13</b>	-	28	-	nC
$Q_{gs}$	gate-source charge		-	2.3	-	nC
$Q_{gd}$	gate-drain (Miller) charge		-	6.1	-	nC
$C_{iss}$	input capacitance	$V_{GS} = 0 \text{ V}; V_{DS} = 10 \text{ V}; f = 1 \text{ MHz}$ ; <b>Figure 11</b>	-	1478	-	pF
$C_{oss}$	output capacitance		-	161	-	pF
$C_{rss}$	reverse transfer capacitance		-	128	-	pF
$t_{d(on)}$	turn-on delay time	$V_{DD} = 15 \text{ V}; I_D = 1 \text{ A}; V_{GS} = 4.5 \text{ V}; R_G = 6 \Omega$	-	15	-	ns
$t_r$	rise time		-	23	-	ns
$t_{d(off)}$	turn-off delay time		-	56	-	ns
$t_f$	fall time		-	30	-	ns
<b>Source-drain diode</b>						
$V_{SD}$	source-drain (diode forward) voltage	$I_S = 4 \text{ A}; V_{GS} = 0 \text{ V}$ ; <b>Figure 12</b>	-	0.67	1.2	V
$t_{rr}$	reverse recovery time	$I_S = 4 \text{ A}; dI_S/dt = -100 \text{ A}/\mu\text{s}$ ; $V_R = 30 \text{ V}$	-	50	-	ns
$Q_r$	recovered charge	$V_{GS} = 0 \text{ V}$	-	19	-	nC




**Fig 5.** Output characteristics: drain current as a function of drain-source voltage; typical values.




$T_j = 25 \text{ }^\circ\text{C}$  and  $150 \text{ }^\circ\text{C}$ ;  $V_{DS} > I_D \times R_{DSon}$

**Fig 6.** Transfer characteristics: drain current as a function of gate-source voltage; typical values.




**Fig 7.** Drain-source on-state resistance as a function of drain current; typical values.




$$a = \frac{R_{DSon}}{R_{DSon}(25 \text{ }^\circ\text{C})}$$

**Fig 8.** Normalized drain source on-state resistance factor as a function of junction temperature.




$I_D = 1 \text{ mA}; V_{DS} = V_{GS}$

**Fig 9.** Gate-source threshold voltage as a function of junction temperature.




$T_j = 25^{\circ}\text{C}; V_{DS} = 5 \text{ V}$

**Fig 10.** Sub-threshold drain current as a function of gate-source voltage.




$V_{GS} = 0 \text{ V}; f = 1 \text{ MHz}$

**Fig 11.** Input, output and reverse transfer capacitances as a function of drain-source voltage; typical values.



$T_j = 25^{\circ}\text{C}$  and  $150^{\circ}\text{C}; V_{GS} = 0 \text{ V}$

**Fig 12.** Source (diode forward) current as a function of source-drain (diode forward) voltage; typical values.



$I_D = 5$  A;  $V_{DD} = 16$  V

Fig 13. Gate-source voltage as a function of gate charge; typical values.

## 6. Package outline

TSSOP8: plastic thin shrink small outline package; 8 leads; body width 4.4 mm

SOT530-1




Fig 14. SOT530-1 (TSSOP8).

## 7. Revision history

Table 5: Revision history

Rev	Date	CPCN	Description
01	20021220	-	Product data (9397 750 10833)

## 8. Data sheet status

Level	Data sheet status <sup>[1]</sup>	Product status <sup>[2][3]</sup>	Definition
I	Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
II	Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
III	Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN).

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.

[3] For data sheets describing multiple type numbers, the highest-level product status determines the data sheet status.

## 9. Definitions

**Short-form specification** — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

**Limiting values definition** — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

**Application information** — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

**Right to make changes** — Philips Semiconductors reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. When the product is in full production (status 'Production'), relevant changes will be communicated via a Customer Product/Process Change Notification (CPCN). Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no licence or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

## 11. Trademarks

TrenchMOS — is a trademark of Koninklijke Philips Electronics N.V.

## 10. Disclaimers

**Life support** — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors

## Contact information

For additional information, please visit <http://www.semiconductors.philips.com>.

For sales office addresses, send e-mail to: [sales.addresses@www.semiconductors.philips.com](mailto:sales.addresses@www.semiconductors.philips.com).

Fax: +31 40 27 24825

## Contents

<b>1</b>	<b>Product profile</b>	<b>1</b>
1.1	Description	1
1.2	Features	1
1.3	Applications	1
1.4	Quick reference data	1
<b>2</b>	<b>Pinning information</b>	<b>1</b>
<b>3</b>	<b>Limiting values</b>	<b>2</b>
<b>4</b>	<b>Thermal characteristics</b>	<b>4</b>
4.1	Transient thermal impedance	4
<b>5</b>	<b>Characteristics</b>	<b>5</b>
<b>6</b>	<b>Package outline</b>	<b>9</b>
<b>7</b>	<b>Revision history</b>	<b>10</b>
<b>8</b>	<b>Data sheet status</b>	<b>11</b>
<b>9</b>	<b>Definitions</b>	<b>11</b>
<b>10</b>	<b>Disclaimers</b>	<b>11</b>
<b>11</b>	<b>Trademarks</b>	<b>11</b>

© Koninklijke Philips Electronics N.V. 2002.

Printed in The Netherlands

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Date of release: 20 December 2002

Document order number: 9397 750 10833



**PHILIPS**

*Let's make things better.*