

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

PANDUIT	STUD SIZE	DIMENSIONS in.						
PART NUMBER		A ±.040	W ±.010	C *.015	M ±.040	H *•010		
PN10-5SLF	#5	.86 (21.84)	.25 (6.35)	.22 (5.59)	.75 (19.05)	.12 (3.05)		
PN10-6SLF	#6	.86 (21.84)	.25 (6.35)	.22 (5.59)	.75 (19.05)	.14 (3.56)		
PN10-8SLF	#8	.92 (23.37)	.29 (7.37)	.26 (6.60)	.79 (20.07)	.16 (4.06)		
PN10-10SLF	#10	.92 (23.37)	.33 (8.38)	.26 (6.60)	.79 (20.07)	.19 (4.83)		
PN10-14SLF	1/4"	1.01 (25.65)	.45 (11.43)	.33 (8.38)	.85 (21.59)	.25 (6.35)		

NOTES:

- 1. UL LISTED AND CSA CERTIFIED FOR:
 - A. 300V. MAX. VOLTAGE RATING
 - B. #12-10 AWG STRANDED COPPER WIRF
 - C. 221° F (105° C) MAX. TEMP. RATING
- 2. MATERIAL:
 - A. STAMPING .04" (1.02) THK COPPER, TIN PLATED
 - B. HOUSING NYLON, YELLOW
 - C. SLEEVE BRASS, TIN PLATED
- 3. PACKAGE QTY: STD. PKG. 50 BULK PKG. 500
- 4. DIMENSIONS IN BRACKETS ARE IN MILLIMETERS
- 5. INSTALLATION TOOLS:
 A. UL LISTED AND CSA CERTIFIED:
 CT-550, CT-1550 & CT-1551



LISTED 587H E52164



CERTIFIED LR31212

М

A41250_05

H DIA

TERMINAL

C RAD

SERRATED BARREL

SLEEVE

BEVELED

EDGE

HOUSING

.225 (5.72)

MAX. WIRE

INSUL. DIA.

05	1/01	KMD		CAD FILE SPEC. WAS N41250AA_PCD_04							
04	5/99	ED		UPDATED "A"&"M" DIM.S, AND MODIFIED DIMENSIONAL TOLERANCES				CORP. TINLEY PARK, ILLINOIS		TINLEY PARK, ILLINOIS	
				FILESPEC WAS: A41250_03							SULATED SHORT
03	4/99	JKD	SKB ADDED CT-1550 & CT-1551 TO NOTE 5 07581 JCJ CTN INSULATION [
REV	DATE	BY	СНК	DESCRIPTION	ECN	APP	PM	DRAWN BY	CJH	NONE	DRAWING NO. A41250