imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Flat Pan-Post[™] Standoffs

• Standard EIA hole spacing allows product to be mounted with user supplied screws up to 1/4" diameter

.61 (15.5)

1.50

(38.1) REF

- · Organize cables in standard cabinets and racks
- Mounting method: 1/4" (M6) screw
- · Use where space is limited
- · For indoor use only



A. System **Overview**

B1.

Cable Ties

B2. Cable Accessorie

B3.

Stainless **Steel Ties**

C1.

Wiring Duct

D1. Terminals

D2. Power Connectors

D3. Grounding

Connectors

E1. Labeling Systems


E2.

Labels


E3.

Pre-Printed & Write-On

Markers



.28 (7.2)




C2. Surface Raceway	Part Number	Used with Cable Ties‡	Material	Color	Mounting Method	Std. Pkg. Qty.	Std. Ctn. Qty.
,	PPF2S-S25-V		Nylon 6.6		Two 1/4" (M6) screws	5	100
C3. Abrasion Protection C4. Cable	PPF2S-S25-V69	M, I, S	Flame Retardant Nylon 6.6				
	PPF2SV-S25-V	M, I, S, HS, LH, H,	Nylon 6.6	Natural			
	PPF2SV-S25-V69	HLM, HLS	Flame Retardant Nylon 6.6				

‡Cable Tie Cross Section Sizes: M = Miniature, I = Intermediate, S = Standard, HS = Heavy-Standard, LH = Light-Heavy, H = Heavy, HLM = Miniature Tak-Ty® Hook & Loop Ties and HLS = Standard Tak-Ty® Hook & Loop Ties .

Right Angle Bases

• Support cable above the mounting surface





	Used with Cable	Max. Flat Cable Width		Length A					Mounting	Std. Pkg.	Std. Ctn.
Part Number	Ties‡	In.	mm	In.	mm	Material	Color	Environment	Method	Qty.	Qty.
RAFCBI1-S6-C20	I	1.00	25.4	1.75	44.4	Nylon 6.6	Black	Indoors	#6 (M3) Screw	100	1000
RAFCBI2-S6-C20	I	2.00	50.8	2.78	70.6						
RAFCBI3-S6-C20	Ι	3.00	76.2	3.81	96.8						

‡Cable tie cross section sizes: I = Intermediate.

E5. Lockout/ Tagout & Safety Solutions

> F. Index