

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








P295 Class Y1, 500 VAC



Sample Kit Contents

KEMET	Capacitance	D	imensions in m	m	Lead	dV/dt	Quantity	
Part Number	Value (µF)	В	Н	L	Spacing (p)	(V/µs)		
P295BE471M500A	0.00047	5.5	12.5	18.0	15	2000	10	
P295BE681M500A	0.00068	5.5	12.5	18.0	15	2000	10	
P295BE102M500A	0.001	5.5	12.5	18.0	15	2000	10	
P295BJ152M500A	0.0015	6.5	12.5	18.0	15	2000	10	
P295BJ182M500A	0.0018	6.5	12.5	18.0	15	2000	10	
P295BJ222M500A	0.0022	6.5	12.5	18.0	15	2000	10	
P295BL252M500A	0.0025	7.5	14.5	18.0	15	2000	10	
P295BL272M500A	0.0027	7.5	14.5	18.0	15	2000	10	
P295BL332M500A	0.0033	7.5	14.5	18.0	15	2000	10	
P295BQ392M500A	0.0039	8.5	16.0	18.0	15	2000	10	
P295BQ472M500A	0.0047	8.5	16.0	18.0	15	2000	10	

Dimensions - Millimeters





Size Code	p		В		н		L		d	
	Nominal	Tolerance								
BE	15.0	+/-0.4	5.5	Maximum	12.5	Maximum	18.0	Maximum	0.8	+/-0.05
BJ	15.0	+/-0.4	6.5	Maximum	12.5	Maximum	18.0	Maximum	0.8	+/-0.05
BL	15.0	+/-0.4	7.5	Maximum	14.5	Maximum	18.0	Maximum	0.8	+/-0.05
BQ	15.0	+/-0.4	8.5	Maximum	16.0	Maximum	18.0	Maximum	0.8	+/-0.05
Note: See Ordering Options Table for lead length (LL) options.										