

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








## **P409 Integrated Resistor Class X2, 275 VAC**



## **Sample Kit Contents**

KEMET	Capacitance	Di	mensions in m	m	Lead	Resistance	Quantity	
Part Number	Value (µF)	В	Н	L	Spacing (p)	(Ω)		
P409QM473M275AH470	0.047	7.3	13.0	18.5	15.2	47	10	
P409QM473M275AH101	0.047	7.3	13.0	18.5	15.2	100	10	
P409CE104M275AH220	0.1	7.6	14.0	24.0	20.3	22	10	
P409CE104M275AH101	0.1	7.6	14.0	24.0	20.3	100	10	
P409CP224M275AH220	0.22	11.3	16.5	24.0	20.3	22	10	
P409CP224M275AH101	0.22	11.3	16.5	24.0	20.3	100	10	
P409CP224M275AH221	0.22	11.3	16.5	24.0	20.3	220	10	
P409EJ224M275AH331	0.22	12.1	19.0	30.5	25.4	330	10	
P409EL474M275AH330	0.47	15.3	22.0	30.5	25.4	33	10	
P409EL474M275AH221	0.47	15.3	22.0	30.5	25.4	220	10	

## **Dimensions - Millimeters**





Size Code	р		В		Н		L		d	
	Nominal	Tolerance								
QM	15.2	+/-0.4	7.3	Maximum	13.0	Maximum	18.5	Maximum	0.8	+/-0.05
CE	20.3	+/-0.4	7.6	Maximum	14.0	Maximum	24.0	Maximum	0.8	+/-0.05
CP	20.3	+/-0.4	11.3	Maximum	16.5	Maximum	24.0	Maximum	0.8	+/-0.05
EJ	25.4	+/-0.4	12.1	Maximum	19.0	Maximum	30.5	Maximum	1.0	+/-0.05
EL	25.4	+/-0.4	15.3	Maximum	22.0	Maximum	30.5	Maximum	1.0	+/-0.05
Note: See Ordering Options Table for lead length (LL) options.										