



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



PRC20 Thermocouple Calibrator



Source and measure 8 thermocouple type devices (J, K, T, E, C, R, S and N) with one meter that provides precision output displayed as °C/°F or mV.

Applications include:

- Lab and Field Calibration and Verification Operations of Sensors, Thermocouple Probes, Controllers, Panel meters & Testing tools.
- Engineering Research and Design
- Manufacturing and Test Engineering
- HVAC
- Temperature Control Process Troubleshooting



Features

- Palm-sized double molded housing and large dot-matrix digital backlit LCD with thermocouple type indication
- High accuracy calibration function simulates precision thermocouple outputs for use in calibrating thermometers, transmitters, controllers or recorders
- Displays output in terms of millivolts or temperature based on thermocouple tables
- Standard mini-thermocouple input
- Large battery bank for extended work cycle
- Up to five user adjustable calibration presets
- External power adapter for continuous work cycle

Specifications	Range	Basic Accuracy
Thermocouple		
Type J	-58 to 1832°F (-50 to 1000°C)	0.05% rdg ±1°
Type K	-58 to 2498°F (-50 to 1370°C)	0.05% rdg ±1°
Type T	-184 to 752°F (-120 to 400°C)	0.05% rdg ±1°
Type E	-58 to 1382°F (-50 to 750°C)	0.05% rdg ±1°
Type C	32 to 3182°F (0 to 1750°C)	0.05% rdg ±1°
Type R/S	32 to 3182°F (0 to 1750°C)	0.05% rdg ±1°
Type N	-58 to 2372°F (-50 to 1300°C)	0.05% rdg ±1°
Voltage	-10.00mV to +60.00mV 10µV	10µV ±1d
Resolution	0.1° (up to 999.9) or 1° (over 999.9) for J, K, T, E ; 1° for R, N; 0.5° for C, S	
Input Impedance	10 MΩ	
Sampling Time	4 times/second	
Meter Dims (LxWxH)	6.3" x 3.2" x 1.7" (159 x 80 x 44mm)	
Meter Wt	8oz (225g) - not including battery weight	

Ordering

- PRC20Thermocouple Calibrator
- PRC20-NISTPRC20 with Certificate of Calibration Traceable to NIST



Complete with Thermocouple calibration cable with subminiature connectors, standard calibration cable with subminiature connectors, 100V-240V AC Universal Adaptor with 4 plugs, 6 x 1.5V AA batteries, and hard carrying case

