

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









Power It! 7-Outlet Power Strip, 12-ft Cord, Black Housing

MODEL NUMBER: PS712B





Highlights

- 7 outlets
- 12 ft power cord
- Illuminated on/off switch
- 15 amp circut breaker
- · Keyhold mounting slots

Package Includes

- PS712B Power Strip
- Instruction manual and warranty information

Description

Tripp Lite's PS712B power strip offers reliable, convenient and cost-effective power distribution for applainces, power tools, lighting and other electrical equipment. PS712B offers 7 total outlets, 12 foot cord. Attractive black housing with keyhole mounting slots and 1 designated transformer plug outlet. Multioutlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket.

PLUG/OUTLETS: Input: NEMA5-15P/Output: 7 NEMA5-15R/12 ft. AC line cord ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle) FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet

Features

- 7 outlets / 12-ft cord
- · Attractive black housing
- EMI/RFI noise filtering
- Can accommodate 1 transformer without blocking remaining outlets
- Keyhole supports for wall mounting

Specifications

OVERVIEW	
UPC Code	037332175212
ОИТРИТ	





Frequency Compatibility	50 / 60 Hz
Output Receptacles	(7) 5-15R
Output (Watts)	1800
Circuit Breaker (amps)	15
Transformer Accommodation	Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 4 transformers total
Outlet Orientation	Single row
Right-Angle Outlets	No
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Recommended Electrical Service	120V (110-125V)
Input Connection Type	NEMA 5-15P
Input Cord Length (ft.)	12
Input Cord Length (m)	3.66
Input Cord Gauge Type	14 gauge, SJT
Voltage Compatibility (VAC)	120
Maximum Surge Amps	72000
USER INTERFACE, ALERTS & CON	ITROLS
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch
DATALINE SURGE SUPPRESSION	
Cable (Coax) Protection	
Janio (Journ) i Totobilott	No
Network (Ethernet) Protection	
	No
Network (Ethernet) Protection	No
Network (Ethernet) Protection PHYSICAL	No No
PHYSICAL Shipping Dimensions (hwd / in.)	No No 2.50 x 4.90 x 13.80
PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm)	No No 2.50 x 4.90 x 13.80 6.35 x 12.45 x 35.05
PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.)	No No 2.50 x 4.90 x 13.80 6.35 x 12.45 x 35.05 1.90
Network (Ethernet) Protection PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg)	No No 2.50 x 4.90 x 13.80 6.35 x 12.45 x 35.05 1.90 0.86
PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Unit Dimensions (hwd / in.)	No No 2.50 x 4.90 x 13.80 6.35 x 12.45 x 35.05 1.90 0.86 1.32 x 2.05 x 11.69
PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Unit Dimensions (hwd / in.) Unit Dimensions (hwd / cm)	No No 2.50 x 4.90 x 13.80 6.35 x 12.45 x 35.05 1.90 0.86 1.32 x 2.05 x 11.69 3.35 x 5.21 x 29.69
PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Unit Dimensions (hwd / cm) Unit Dimensions (hwd / cm) Unit Weight (lbs.)	No No 2.50 x 4.90 x 13.80 6.35 x 12.45 x 35.05 1.90 0.86 1.32 x 2.05 x 11.69 3.35 x 5.21 x 29.69 1.76
PHYSICAL Shipping Dimensions (hwd / in.) Shipping Dimensions (hwd / cm) Shipping Weight (lbs.) Shipping Weight (kg) Unit Dimensions (hwd / cm) Unit Dimensions (hwd / cm) Unit Weight (lbs.) Unit Weight (kg)	No No 2.50 x 4.90 x 13.80 6.35 x 12.45 x 35.05 1.90 0.86 1.32 x 2.05 x 11.69 3.35 x 5.21 x 29.69 1.76 0.80



Tripp Lite1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Color (AC Line Cord)	Black	
Outlets Measurement (Center to Center)	Distance between standard outlets = 29mm; Distance between last standard outlet and transformer outlet = 33mm	
Keyhole Slot Mounting Measurement (Center to Center)	Distance between slots = 151mm; Distance between slot height = 24mm	
CERTIFICATIONS		
Additional International Approvals	RoHS	
NOM (Mexico)	NOM	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies