



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





15 Watt Fixed Wall Plug Series Adapter Meets Level VI Requirements



Features

- Limited Power Source (LPS)
- Class B EMI
- Level VI Compliant
- Class II Double Insulated
- High Efficiency
- Low Cost

Applications

- Wireless Communications
- Peripherals
- Portable Equipment
- PDA

Safety Approvals

- cUL/UL

Mechanical Characteristics

- Length: 71.7mm (2.82in)
- Width: 50mm (1.97in)
- Height: 33.2mm (1.31in)
- Weight: 145g (5.12oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple ⁽¹⁾ P-P (max.)	Regulation Line & Load	Efficiency Level
		Min.	Max.			
PSC15A-050	5V	0A	3.0A	100mV	±5%	VI
PSC15A-060	5.9V	0A	2.5A	100mV	±5%	VI
PSC15A-075	7.5V	0A	2.0A	100mV	±5%	VI
PSC15A-090	9V	0A	1.67A	120mV	±5%	VI
PSA15A-120P6	12V	0A	1.25A	100mV	±5%	VI
PSA15A-150P6	15V	0A	1.0A	100mV	±5%	VI
PSA15A-240P6	24V	0A	0.65A	200mV	±5%	VI
PSA15A-480P6	48V	0A	0.31A	400mV	±5%	VI

(1) Measured after 30 minutes with by-pass capacitors 0.1uF/10uF at output connector terminal and oscilloscope set at 20Mhz.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

Input:

AC Input Voltage Rating
100 to 240V AC

AC Input Voltage Range
90 to 264V AC

AC Input Frequency
47 to 63Hz

Input Current
0.5A (RMS) maximum at 120V AC
0.25A (RMS) maximum at 240V AC

Leakage Current
0.25mA maximum at all line conditions

Inrush Current
<40A for 120V AC at maximum load
<60A for 240V AC at maximum load
(Cold start at ambient 25°C)

Input Power Saving
0.1W maximum at no load

Output:
Efficiency
US DOE Level VI

Environmental:
Temperature
Operation 0 to +40°C
Non-operation -40 to +85°C

Humidity 20 to 90%

Emissions
FCC Class B
EN55022 Class B

Immunity
IEC61000-4-2
IEC61000-4-3
IEC61000-4-4
IEC61000-4-5
IEC61000-4-6
IEC61000-4-8
IEC61000-4-11
EN61000-3-2

Hold-up Time
8mS minimum at 120V AC and maximum load

Over-Voltage Protection
Zener clamping if voltage exceeds 120% of limit

Over-Current Protection
Output equipped with short circuit protection – auto-restart

Short-Circuit Protection
Output can be shorted without damage

Dielectric Withstand (Hi-pot) Test
Primary to Secondary: 3000V AC for 1 min., 10mA

DC Output Connector
2.1 x 5.5mm Center Positive Barrel

Dimension Diagram Unit: mm (inch)

