



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





2.75W Compact Fixed Blade Charger (United Kingdom) Ecodesign Compliant USB Adapter



★★★★★
Standby Power



Features

- Fixed Blade
- CC & CV control
- Ecodesign ErP Directive 2009/125/EC level 2 annex 1b Compliant
- Low Cost
- 5 Star Standby power <0.03W
- No Y Cap
- Halogen Free

Applications

- MPEG Players
- PDA
- Personal Electronics
- Digital Camera

Safety Approvals

- CE
- IEEE1725 Approved

Mechanical Characteristics

- Length: 49mm (1.93in)
- Width: 43mm (1.65in)
- Height: 21.0mm (0.87in)
- Weight: 80g (3oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max)	Regulation	
		Min.	Max.		Line	Load
PSM03K-050Q	5V	0A	0.55A	100mV	±5%	

Note: (1) Measured after 10 minutes with by-pass capacitors 0.1uF // 10uF at output connector terminal and oscilloscope set at 20MHz.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

INPUT:

AC Input Voltage Rating
100 to 240VAC

AC Input Voltage Range
90 to 264VAC

AC Input Current
0.1A(RMS) max.

Leakage Current
0.25mA max. @ 230VAC

Inrush Current (cold)
<30A for 120VAC at max. load
<60A for 240VAC at max. load
(Cold start @ ambient 25°C)

Input Power Saving
<0.15W max. @ 230VAC at no load

OUTPUT:

Power
2.75W Maximum

Efficiency
Meets Level V Efficiency Requirements
63.7% minimum average efficiency

No-Load Power Saving
0.03W maximum at 115VAC/230VAC

Hold-up Time
10mS min. @ 120VAC and max. load

Over-voltage Protection
>120%, Zener Clamp

ENVIRONMENTAL:

Temperature
Operation -10 to +40°C
Non-operation -40 to +85°C

Humidity
Operation 10 to 90%

Immunity
ESD: EN61000-4-2. Level 4
Surge: EN61000-4-5. Level 4
Harmonic: EN61000-3-2
Flicker: EN61000-3-3

Emissions
FCC Class B
EN55022 Class B

Dielectric Withstand (Hi-pot) Test
Primary to Secondary: 3000VAC

Insulation Resistance
Primary to Secondary: 7M ohm 500VDC

MTBF
200K hours minimum at 120VAC, max load
(measured at ambient 25°C)

DC Output Connector
USB A
D+ and D- pins shorted together inside the charger

Dimension Diagram Unit: mm

