



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





8W Interchangeable Plug Series with Micro-USB Connector PSM08R Adapter Meets EISA and CEC Requirements



Features

- Double Insulated
- Field Changeable AC Plugs
- Efficiency Level IV Compliance
- 5% NL-FL Regulation
- Low Leakage Current
- Micro-USB Connector
- Class B EMI
- CCCV

Applications

- Wireless Communications
- Networking
- Portable Equipment
- Peripherals

Safety Approvals

- cUL/UL
- TUV
- SAA
- CCC
- CE
- C-Tick
- PSE

Mechanical Characteristics

- Length: 71.7mm (2.82in)
- Width: 45mm (1.77in)
- Height: 29.79mm (1.17in)
- Weight: 128g (4.52oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple ⁽¹⁾ P-P (max.)	Regulation Line & Load	Efficiency Level
		Min.	Max.			
PSM08R-050(M)	5V	0A	1.6A	100mV	±5%	IV

(1) Measured with by-pass capacitors 0.1uF/10uF at output connector terminal and oscilloscope set at 20MHz. (Tested oscilloscope after waiting 1 minute).

- Interchangeable clips sold separately.

Input:

AC Input Voltage Rating

100 to 240V AC

AC Input Voltage Range

90 to 264V AC

AC Input Frequency

47 to 63Hz

Input Current

0.3A (RMS) maximum at 120V AC

0.15 (RMS) maximum at 240V AC

Leakage Current

25mA maximum at 264V AC

Inrush Current

40 to 60A for 120V AC at maximum load (varies in voltage), (cold start at ambient 25°C)

Input Power Saving

0.3W maximum at 240V AC

Output:

Efficiency

69% minimum using ENERGY STAR method

Hold-up Time

10mS minimum at 120V AC and maximum load

Over-Voltage Protection

120%, Zener Clamping

Short-Circuit Protection

120%, auto restart.

Environmental:

Temperature

Operation 0 to +50°C

Non-operation -20 to +75°C

Humidity 0 to 90%

Emissions

FCC Class B

EN55022 Class B

Immunity

EN50082-1: (EN55024)

EN61000-4-2 Level 4

EN61000-4-3 Level 2

EN61000-4-4 Level 2

EN61000-4-5 Level 3

EN61000-4-6 Level 2

EN61000-4-8 Level 1

EN61000-4-11

Dielectric Withstand (Hi-pot) Test

Primary to Secondary: 3000V AC for 1 min., 10mA

DC Output Connector

Micro USB

Dimension Diagram Unit: mm (inch)

