

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Weller Power Unit for WTCPT Temperature Controlled Soldering Station



	4∢ previous	print	close	next 🕨	
Product Details					
	Catalog No.		PU120T		
	UPC Code		037103001115		
	Wattage		60 W		
	Soldering Pencil(s)		TC201T		
	Temperature Range		600° F to 800° F		
	Voltage Input/Output		120 V/24 V PTA 7 PH1201ESD Not Specified		
	Supplied Tip(s)				
	Iron Stand				
	Temperature Accuracy				
Packaging Literature Tech. Spec. Low Res. Image High Res. Image		Industrial Box/Carton			
		T550733.pdf			
		Solder_Safety_Warnings.pdf			
		PU120T_100.jpg			
		PU120T 300.jpg			
	Stock Item	ľ	Normal St	ock Item	

Package Details (Dimensions)

Email this Page

Product Features:

- Voltage: 120V (input); 24V (output)
- Power consumption: 60 watts
- Temperature range 600°F 800°F (316°C 427°C)
- Footprint: 4 1/2" x 5 15/16" x 3 5/8" (114mm x 150mm x 91mm)
- Weight: 3.9 lb (1.78 kg)
- ESD Safe? Yes