



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



TX6A-SD™ 10Gig™ U/UTP Copper Cable with MaTriX Technology

specifications

Category 6A/Class E_A cable is constructed of 26 AWG copper conductors with FEP Plenum (CMP), PVC Riser (CMR), HDPE Low Smoke Zero Halogen (LSZH), or PVC (CM) insulation. The copper conductors are twisted in pairs and separated by a cross-divider. All four pairs are surrounded by MaTriX tape and a flame retardant jacket. The patented MaTriX tape suppresses the effect of alien crosstalk allowing 10 Gb/s transmission. The innovative cable design provides installation flexibility as cables can be routed in tight bundles through pathways and spaces.



technical information

Category 6A/Class E_A channel performance:	Exceeds electrical and alien crosstalk performance requirements of ANSI/TIA-568-C.2 Category 6A and ISO 11801 Class E _A standards for supporting 10GBASE-T transmission over twisted-pair cabling systems in a 4-connector configuration *Note: The cable utilizes 26 AWG conductors which does not meet the 24 to 22 AWG conductor size of horizontal cable in ANSI/TIA-568-C.2, resulting in increased attenuation which de-rates the maximum channel distance to 70 meters (229 feet)
Cable diameter:	0.240 in. (6.1mm) nominal
Conductors/insulators:	26 AWG solid copper insulated with FEP (CMP), flame retardant PVC (CMR), HDPE (LSZH), or PVC (CM)
Flame rating:	FEP Plenum (CMP): NFPA 262 PVC Riser (CMR): UL 1666 HDPE (LSZH-1): IEC 60332-1, 60754-2, 61034-2; EN 50575: Euroclass Dca - s2, d2, a1 HDPE (LSZH-3): IEC 60332-3-25 (-3d), NBN C 30-004 (F2), 60754-2, 61034-2; EN 50575: Euroclass Dca - s2, d2, a1 PVC (CM): IEC 60332-1 and UL 1685
PoE compliance:	Meets IEEE 802.3af, IEEE 802.3at and IEEE 802.3bt for PoE applications
Installation tension:	25 lbf (110 N) maximum
Temperature rating:	32°F to 140°F (0°C to 60°C) during installation -4°F to 167°F (-20°C to 75°C) during operation
Cable jacket:	FEP Plenum (CMP)/PVC (CM): Flame retardant PVC PVC Riser (CMR)/HDPE (LSZH): Low smoke flame retardant PVC HDPE (LSZH): PVC Free
Cable weight:	FEP Plenum: 38 lbs./1000 ft. (17 kg/305m) PVC Riser (CMR)/HDPE (LSZH)/PVC (CM): 30 lbs./1000 ft. (14 kg/305m)
Packaging:	1000 ft. (305m) on a reel FEP Plenum (CMP): 42 lbs./1000 ft. (19 kg/305m) PVC Riser (CMR): 34 lbs./1000 ft. (15 kg/305m) HDPE (LSZH)/PVC (CM): 46 lbs./1000 ft. (21 kg/305m) Package tested to ISTA procedure 1A

key features and benefits

Interoperable	Compatible with components of the TX6A™ 10Gig™ U/UTP Copper Cabling System with MaTriX Technology (100 meter solution) for increased design flexibility
MaTriX Technology PATENTED	Provides superior suppression of alien crosstalk (PSANEXT and PSAACRF); improves the installation flexibility by allowing cable combing in existing pathways without compromising performance
Superior headroom warranty	Provides the highest margins above the industry standard for both electrical and alien crosstalk performance
Smaller cable diameter than most Category 6 cable and round, flexible design	Allows efficient use of pathways and spaces by improving fill capacity and reducing required bend radius resulting in easier cable routing and management
Extended temperature range	Allows operation in 75°C (167°F) ambient environment providing error-free performance in high density cabinets and large cable bundles for running PoE Plus applications
Cross-divider	Separates pairs for exceptional cable performance
Descending length cable markings	Easy identification of remaining cable to reduce installation time and cable scrap

applications

The TX6A-SD™ 10Gig™ U/UTP Copper Cable with MaTriX Technology is a component of the TX6A™ 10Gig™ Copper Cabling System. Interoperable and backward compatible, this end-to-end system provides design flexibility to protect network investments well into the future.

Key applications include:

- 10GBASE-T Ethernet
- Data center I/O consolidation
- Data center server virtualization
- Back-bone aggregation
- Parallel processing and high speed computing

www.panduit.com

TX6A-SD™ 10Gig™ U/UTP Copper Cabling System

TX6A-SD™ 10Gig™ U/UTP Copper Cable

Plenum:	PUP6ASD04*-UG
Riser:	PUR6ASD04*-CG
LSZH (60332-1):	PUL6ASD04 [‡]
LSZH (60332-3):	PUZ6ASD04 [‡]
CM:	PUC6ASD04*-EG

Mini-Com® TX6A™ 10Gig™ UTP Jack Modules

Jack module:	CJ6X88TG**
Shuttered jack module:	CJD6X88TG**

TX6A-SD™ 10Gig™ UTP Patch Cords

CM (foot lengths):	UTP6ASD^BU
CM (meter lengths):	UTP6ASD^^MBU
LSZH (meter lengths):	UTP6ASDL^^MBU

Mini-Com® Angled Modular Patch Panels

24-port, 1 RU:	CPPA24FMWBLY
48-port, 2 RU:	CPPA48FMWBLY
72-port, 2 RU:	CPPLA72WBLY

Mini-Com® Flat Modular Patch Panels

24-port, 1 RU:	CPP24FMWBLY
48-port, 1 RU:	CPP48HDWBLY
48-port, 2 RU:	CPP48FMWBLY
72-port, 2 RU:	CPP72FMWBLY

For additional modular patch panels reference www.panduit.com

Cable Prep Tools

Wire snipping tool:	CWST
Wire stripping tool:	CWST
Cable bundle organizing tool:	CBOT24K

*To designate color, add suffix BU (Blue), WH (White), IG (International Gray) or YL (Yellow). For additional cable colors, contact Customer Service.

‡ To designate color and length, replace [‡] with BU-EG (Blue) or WH-EG (White) to designate color in a Euro pallet with 36 reels, 305m each.

Replace [‡] with BU-CED (Blue) or WH-CED (White) to designate color in a Euro pallet of 36 reels, 500m each.

**To designate color, add suffix IW (Off White), EI (Electric Ivory), IG (International Gray), AW (Arctic White), BL (Black), BU (Blue), RD (Red), YL (Yellow), GR (Green), OR (Orange), or VL (Violet).

^For lengths 3 to 20 feet (increments of one foot) 20, 25, 30, 35 or 40 feet change the length designation in the part number to the desired length. For standard cable colors other than Off White, add suffix BL (Black), BU (Blue), RD (Red), YL (Yellow), GR (Green), OR (Orange), GY (Gray), or VL (Violet) to the end of the part number. For example, the part number for a blue, 15-foot patch cord is UTP6ASD15BU.

^^For lengths 1, 2, 2.5, 3, 5 meters, change the length designation in the part number to the desired length. For standard cable colors other than Off White, add suffix BL (Black), BU (Blue), RD (Red), YL (Yellow), GR (Green), OR (Orange), GY (Gray), or VL (Violet). LSZH patch cable available in Off White or BU (Blue). For example, the part number for a blue, 5-meter patch cord is UTP6ASD5MBU.


Contact Customer Service for bulk packaged and/or keyed jack modules and patch cords.

TX6A-SD™ 10Gig™ U/UTP Copper Cable with MaTriX Technology

additional specifications

Mechanical Test	
<i>Ultimate Breaking Strength</i>	>90 lbf (400 N)
<i>Minimum Bend Radius</i>	4 x cable diameter
Electrical Test	
<i>DC Resistance</i>	<9.38 Ohm per 328 ft. (100m)
<i>DC Resistance Unbalance</i>	<5%
<i>Mutual Capacitance</i>	<5.6 nF per 328 ft. (100m) at 1 kHz
<i>Capacitance Unbalance</i>	<330 pF per 328 ft. (100m) at 1 kHz
<i>Characteristic Impedance</i>	100 Ohm +/-15% up to 100 MHz
<i>Nominal Velocity of Propagation (NVP)</i>	Panduit 67%
<i>Operating Voltage, maximum</i>	80V

cable construction



WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT US/CANADA
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
cs-emea@panduit.com
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
cs-ap@panduit.com
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
cs-japan@panduit.com
Phone: 81.3.6863.6000

PANDUIT LATIN AMERICA
Guadalajara, Mexico
cs-la@panduit.com
Phone: 52.33.3777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
cs-aus@panduit.com
Phone: 61.3.9794.9020

For a copy of Panduit product warranties, log on to www.panduit.com/warranty

For more information

Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com
or by phone: 800.777.3300

PANDUIT®

© 2017 Panduit Corp.
ALL RIGHTS RESERVED.
COSP289--WW-ENG
Replaces WW-COSP198
6/2017