

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







						2								1			
	THIS COF	PY IS	PROV	'IDED	ON A RI	ESTRICTED B	ASIS AND !	S NOT TO BE	USED IN A	NY WAY D	DETRIMEN	ITAL T	O THE	INTERES	STS OF P	PANDUIT CORP.	
	PANDUIT		STUD SIZE DIMENSIONS in. [m						nm]						— W ——		
	PART #		ENGLIS	н М	ETRIC	L ± .03 [0,76]	$W \pm \frac{.01}{[0,25]}$	C ± .02 [0,51]	$M \pm \frac{.03}{[0,76]}$	H± .01		A				STAME	PING
	PV10-6FB		#6		M3, 5	.99 [25,2]	.30 [7,6]	.22 [5,6]	.78 [19,8]	.15 [3,8]	1	-	A				
T	PV10-8FB		#8		M4	1.00 [25,4]	.30 [7,6]	.22 [5,6]	.78 [19,8]	.17 [4,3]					\X	Н В	ΑI
	PV10-10F	3	#10			1.04 [26,4]	.34 [8,6]	.22 [5,6]	.78 [19,8]	.20 [5,0]]					C RAL	
-	PMV6-5FE				M5	1.02 [25,9]	.38 [9,7]	.24 [6,2]	.79 [20,1]	.21 [5,3]				7			
	PV10-14FI	В	1/4"		M6	1.13 [28,7]	.49 [12,5]	.32 [8,1]	.88 [22,4]	.27 [6,9]]			10		NOUG I	NIC
	NOTES:	1											M L			HOUSII	NG
	1. USE			AWG	[4 ₋ 0-	6.0 mm²1	SOLID OR	STRANDER) COPPER	WIRF						FUNNEL	
	B.	#12-10 AWG [4,0-6,0 mm²] SOLID OR STRANDED C 221°F [105°C] MAX. OPERATING TEMPERATURE 600 V. MAX. VOLTAGE RATING								., 111						WIRE E	
	2. INS	STAL	LAT I	ON T	FOOLS:	AGE KAIII	לטע									CAF STF	RRIER
	Α.	PRE	SSES	# CF	9-871	00 040							.)			\ 1
	В. С.	DIE	LICA Ins	ERTS	6: CD-	00, CA9 800-3, C[09-3B				,		(- N			0.1
						11/32 +1/32		1						4		.23 [5,8 —— MAX. WIF	8 J RE
	4. MA7	TER I	AL:			· ·	ū									INSUL. [
	A. B	STA	MPIN	G: ,	.04 " [] /inyi	I,O] THK YELLOW	COPPER,	tin plate	ED								
	5. SEE	- ww	/W . DC	ndu	it.com	FOR PACK	KAGE QUAN	NTITIES			(11)		R	N _®	ПЛ	ת חת חת	\int
						UMBER SUF		NIIVALENT					6				_{_
	O. DIN	/ILI _	, 1 0 1 10	111	BITTOIT	L13 /((L1	VICTIVIO EC	XO I V/\LLINI		1	LISTED		CDII	FIED			
											587H		ERTI LR31	212			
										E	E52164						
										TITLE			D. 8. 8. 1. 4			// NIOLU A TED	
											FORK TERMINALS, 2 PC. VINYL INSULATED, #12-10						
													(. – iu Drawino	2	
										ITEM F	REVISION NAME	N 4407		,03 TOWILIT	100		
										DATASE	ET FILE NAME		'9BA/06			PANDU	
											MATERIAL:						
										אום [UNLESS MENSIONAL	OTHERW TOLEF	HERWISE SPECIF DLERANCES ARE:			HENIALI	
											.x ± .1 [2			± .005 [.	131	SEE NOTES	
3	09.07.12	JBN LCA VMB ADDED METRIC EQUIVALENT. REVISED NOTES. UPDATED DRAWING TO CURRENT STANDARDS.				A4107		×× ± .01 [25]	ANGLES TH P	±5° HIRD ANGLE ROJECTION	Ξ Ι	NG NUMBER: A 4 1 0 7 9				
						-				DRAWN	BY DATE	Ψ	СНК	SCALE		, , , , , , ,	SIZE
ΕV	DATE	BY	CHK	APR		DES	SCRIPTION		EC1	LN		-	_	N.T.S	i.	SHT 1 0F 1	ΙΑ