



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China






Ring Terminal, Vinyl Expanded Insulation

- Expanded wire entry designed to accommodate wire with a larger insulation thickness
- Ring tongue design assures a secure connection in high vibration applications
- Insulation support helps to prevent wire damage in bending applications
- Brazed seam protects terminal barrel from splitting during the crimp process

- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V-0, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up to 600 V per UL 486A/B



Part Number	Wire Range		Color Code	Max. Ins. Dia.		Stud Size		Length		Width		Clearance		Panduit Crimping Tool	Std. Pkg. Qty.	Std. Ctn. Qty.
	AWG	mm ²		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm			
PV14-8RX-C	16 – 14 AWG	1.5 – 2.5	Blue	0.200	5.1	#8	M4	0.96	24.4	0.31	7.9	0.25	6.4	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡	100	500
PV14-10RX-C				0.200	5.1	#10	M5	0.96	24.4	0.31	7.9	0.25	6.4		100	500
PV14-14RX-L				0.200	5.1	1/4"	M6	1.16	29.5	0.46	11.7	0.37	9.4		50	500
PV14-56RX-L				0.200	5.1	5/16"	M8	1.16	29.5	0.46	11.7	0.37	9.4		50	500
PV14-38RX-L				0.200	5.1	3/8"	M10	1.25	31.8	0.53	13.5	0.42	10.7		50	500
PV10-8RX-L	12 – 10 AWG	4.0 – 6.0	Yellow	0.250	6.4	#8	M4	1.10	27.9	0.31	7.9	0.30	7.6	CT-100A‡, CT-600-A‡, CT-1550‡, CT-1551‡, CT-2500‡	50	500
PV10-10RX-L				0.250	6.4	#10	M5	1.10	27.9	0.31	7.9	0.30	7.6		50	500
PV10-14RX-L				0.250	6.4	1/4"	M6	1.29	32.8	0.52	13.2	0.39	9.9		50	500
PV10-56RX-L				0.250	6.4	5/16"	M8	1.29	32.8	0.52	13.2	0.42	10.7		50	500
PV10-38RX-L				0.250	6.4	3/8"	M10	1.35	34.3	0.58	14.7	0.46	11.7		50	500
PV8-10RX-QY	8 AWG	10.0	Red	0.360	9.1	#10	M5	1.52	38.6	0.47	11.9	0.43	10.9	CT-720 with Die Insert CD-720PV8-2‡, CT-2600 with Die Insert CD-2600-PV8‡	25	250
PV8-14RX-QY				0.360	9.1	1/4"	M6	1.52	38.6	0.47	11.9	0.43	10.9		25	250
PV8-56RX-QY				0.360	9.1	5/16"	M8	1.62	41.2	0.59	15.0	0.51	13.0		25	250
PV8-38RX-QY				0.360	9.1	3/8"	M10	1.62	41.2	0.59	15.0	0.51	13.0		25	250
PV8-12RX-XY				0.360	9.1	1/2"	M12	1.74	44.2	0.82	20.8	0.51	13.0		10	100
PV6-10RX-X	6 AWG	16.0	Blue	0.436	11.1	#10	M5	1.61	40.9	0.47	11.9	0.43	10.9	CT-720 with Die Insert CD-720PV8-2‡, CT-2600 with Die Insert CD-2600-PV6‡	10	100
PV6-14RX-X				0.436	11.1	1/4"	M6	1.61	40.9	0.47	11.9	0.43	10.9		10	100
PV6-56RX-X				0.436	11.1	5/16"	M8	1.73	43.9	0.62	15.8	0.51	13.0		10	100
PV6-38RX-X				0.436	11.1	3/8"	M10	1.73	43.9	0.62	15.8	0.53	13.5		10	100
PV4-14RX-E	4 AWG	25.0	Yellow	0.515	13.1	1/4"	M6	1.87	47.5	0.55	14.0	0.53	13.5	CT-720 with Die Insert CD-720PV8-2‡, CT-2600 with Die Insert CD-2600-PV4‡	20	200
PV4-56RX-E				0.515	13.1	5/16"	M8	1.94	49.3	0.68	17.3	0.53	13.5		20	200
PV4-38RX-E				0.515	13.1	3/8"	M10	1.94	49.3	0.68	17.3	0.53	13.5		20	200
PV4-12RX-E				0.515	13.1	1/2"	M12	2.03	51.6	0.86	21.8	0.53	13.5		20	200
PV2-14RX-XY	2 AWG	35.0	Red	0.632	16.1	1/4"	M6	1.94	49.3	0.68	17.3	0.58	14.7	CT-720 with Die Insert CD-720PV8-2‡, CT-2600 with Die Insert CD-2600-PV2‡	10	100
PV2-56RX-XY				0.632	16.1	5/16"	M8	1.94	49.3	0.68	17.3	0.58	14.7		10	100
PV2-38RX-XY				0.632	16.1	3/8"	M10	1.94	49.3	0.68	17.3	0.58	14.7		10	100
PV2-12RX-XY				0.632	16.1	1/2"	M12	2.03	51.6	0.86	21.8	0.58	14.7		10	100

‡UL and CSA approved tooling/product combinations.
 For crimping tool information, see page M.46.
 For the full selection of Panduit Crimping Tools see www.panduit.com.