Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!

Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832
Email & Skype: info@chipsmall.com Web: www.chipsmall.com
Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China

Ring Terminal, Vinyl Insulated – Funnel Entry

Type PV-R

- Insulation support helps to prevent wire damage in bending applications
- Ring tongue design assures a secure connection in high vibration applications
- Brazed seam protects terminal barrel from splitting during the crimp process

- Internal barrel serrations assure good wire contact and maximum tensile strength
- UL Flammability UL 94V-0, maximum insulation temperature 221°F (105°C)
- UL and CSA rated up 600 V per UL 486A/B

Part Number	Wire Range	Color Code	Stock Thickness (In.)	Max. Ins. (In.)	Stud Size	Figure Dimensions (In.)			Recommended Installation Tool	Std. Pkg. Qty.**	Std. Ctn. Qty.
						L	W	C			
PV22-2R-CY*			0.02	0.110	#2	0.68	0.21	0.18		100	1000
PV22-4R-CY*			0.02	0.110	#4	0.68	0.21	0.18	CT-600-A,	100	1000
PV22-6R-CY*	26 – 22 AWG	Yellow	0.02	0.110	#6	0.68	0.21	0.18	CT-1525,	100	1000
PV22-8R-CY*			0.02	0.110	#8	0.78	0.26	0.26	CT-2500	100	1000
PV22-10R-CY*			0.02	0.110	#10	0.78	0.32	0.24		100	1000
PV18-4R-CY			0.03	0.150	#4	0.84	0.25	0.22		100	500
PV18-6R-CY			0.03	0.150	#6	0.86	0.25	0.22		100	500
PV18-8R-CY			0.03	0.150	#8	0.91	0.31	0.26	CT-100A‡,	100	500
PV18-10R-CY	22 – 18 AWG	Red	0.03	0.150	#10	0.94	0.31	0.27	CT-600-A‡,	100	500
PV18-14R-CY			0.03	0.150	1/4"	1.11	0.46	0.37	CT-1550‡,	100	500
PV18-56R-CY			0.03	0.150	5/16"	1.11	0.46	0.39	CT-1551‡,	100	500
PV18-38R-LY			0.03	0.150	3/8"	1.19	0.53	0.42	CT-2500‡	50	500
PV18-12R-LY			0.03	0.150	1/2"	1.42	0.72	0.53		50	500
PV14-4R-C			0.03	0.170	#4	0.84	0.25	0.19		100	500
PV14-6RN-C			0.03	0.170	#6	0.84	0.25	0.19		100	500
PV14-6R-C			0.03	0.170	#6	0.92	0.31	0.25		100	500
PV14-8R-C			0.03	0.170	#8	0.92	0.31	0.25	CT-100A‡,	100	500
PV14-10R-C	16 – 14 AWG	Blue	0.03	0.170	#10	0.92	0.31	0.25	CT-600-A‡,	100	500
PV14-14R-C			0.03	0.170	1/4"	1.12	0.46	0.38	CT-1550‡,	100	500
PV14-56R-C			0.03	0.170	5/16"	1.12	0.46	0.38	CT-1551‡,	100	500
PV14-38R-L			0.03	0.170	3/8"	1.21	0.53	0.43	CT-2500‡	50	500
PV14-12R-L			0.03	0.170	1/2"	1.42	0.72	0.53		50	500
PV10-6R-L			0.04	0.225	#6	1.05	0.31	0.31		50	500
PV10-8R-L			0.04	0.225	#8	1.05	0.31	0.31		50	500
PV10-10R-L			0.04	0.225	#10	1.05	0.31	0.31	CT-100A‡,	50	500
PV10-14R-L	12 – 10 AWG	Yellow	0.04	0.225	1/4"	1.23	0.52	0.38	CT-600-A‡,	50	500
PV10-56R-L			0.04	0.225	5/16"	1.23	0.52	0.38	CT-1550‡,	50	500
PV10-38R-L			0.04	0.225	3/8"	1.31	0.58	0.41	CT-1551‡, CT-2500‡	50	500
PV10-12R-Q			0.04	0.225	1/2"	1.46	0.72	0.53		25	250

*Wire sizes #26 – 22 AWG, are not UL Listed or CSA Certified.
**Bulk packaging may be available, contact Panduit Customer Service for additional information.
‡UL and CSA approved tooling/product combinations. For crimping tool information, see pages D1.83, D1.84, D1.86 and D1.88.