



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## 2400W PowerVerter Plus Industrial-Strength Inverter with 2 Outlets

MODEL NUMBER: PV2400FC



### Description

Continuously supplies up to 2400W of 120V AC power to 2 AC outlets from any 24V battery or automotive DC source. Frequency control locks AC output at 60Hz for operating stability of motor loads. Includes a set of high current DC input terminals for simple, permanent installation. Highly reliable large transformer design specializes in powering motors and other inductive loads with high-current startup needs.

NOTE: To protect against high current draw that may occur during inverter failure, a fuse link rated at 250a should be positioned no more than 18" from the PV2400FC's battery in the positive line.

### Features

- Converts 24V DC battery power to 120V AC power
- 2400W continuous output power
- Peak surge output: OverPower (up to 1 hour), 3600 watts; Double-Boost (up to 10 seconds), 4800W
- Set of 2 bolt-down DC wiring terminals for 24V battery connection; 2 x NEMA 5-15/20R outlets
- Frequency control for operating stability
- High-efficiency operation conserves batteries to prolong run time
- Diagnostic LEDs indicate load level (high, medium, and low) and battery charge (high, medium, and low)
- DC fusing protects inverter against overload
- High-impact polycarbonate housing
- RJ45 port allows connection of APS/PowerVerter Remote Switch (APSRM4)

## Specifications

### Highlights

- Designed for heavy duty and motor loads
- 24V DC input; 120V AC output; 2 outlets
- 2400W continuous output
- Peak surge output: OverPower (up to 1 hour)—3600W; Double-Boost (up to 10 seconds)—4800W
- High-efficiency power conversion
- Automatic overload protection

### Package Includes

- PV2400FC Inverter
- Instruction manual



| <b>OVERVIEW</b>                              |   |
|--|---|
| UPC Code                                     | 037332042200  |
| <b>OUTPUT</b>                                |   |
| Nominal Output Voltage(s) Supported          | 120V  |
| Frequency Compatibility                      | 60 Hz   |
| Output Receptacles                           | (2) 5-15R   |
| Output (Watts)                               | 2400  |
| Continuous Output Capacity (Watts)           | 2400  |
| Peak Output Capacity (Watts)                 | 4800  |
| Output Voltage Regulation                    | Maintains PWM sine wave output voltage of 120 V AC (+/-5%)  |
| Output Frequency Regulation                  | 60 Hz (+/- 0.3 Hz)  |
| Overload Protection                          | Circuit breaker   |
| <b>INPUT</b>                                 |   |
| Recommended Electrical Service               | Requires 24V DC input source capable of delivering 120A for the required duration (when used at full capacity). For automotive applications, professional hardwire installation with 250A battery system fusing is recommended  |
| Maximum Input Amps / Watts                   | Full continuous load - 120A at 24V DC; No load - 2.2A at 24V DC   |
| Input Connection Type                        | Set of 2 bolt-down DC wiring terminals  |
| Input Cord Length Details                    | User supplies cabling; 2/0 gauge or larger recommended  |
| Voltage Compatibility (VDC)                  | 24  |
| <b>BATTERY</b>                               |   |
| DC System Voltage (VDC)                      | 24  |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b> |   |
| Front Panel LEDs                             | Set of 6 LEDs provides continuous status information on load percentage (6 levels reported) and battery charge level (7 levels reported). See manual for sequences  |
| Switches                                     | 3-position on/off/remote switch enables simple on/off power control plus "remote" setting that enables distant on/off control of the inverter system when used in conjunction with optional <a href="http://www.tripplite.com/Remote-Control-Module-Tripp-Lite-PowerVerter-Inverters-Inverter-Chargers~APSRM4">APSRM4</a> accessory |
| <b>PHYSICAL</b>                              |   |
| Shipping Dimensions (hwd / in.)              | 12.90 x 14.40 x 21.30   |
| Shipping Dimensions (hwd / cm)               | 32.77 x 36.58 x 54.10   |
| Shipping Weight (lbs.)                       | 38.60   |
| Shipping Weight (kg)                         | 17.51   |
| Unit Dimensions (hwd / in.)                  | 7.25 x 8.5 x 16.25  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                     |  |
|-------------------------------------|--|
| Unit Dimensions (hwd / cm)          | 18.42 x 21.59 x 41.28  |
| Unit Weight (lbs.)                  | 39   |
| Unit Weight (kg)                    | 17.69  |
| Cooling Method                      | Fan  |
| Material of Construction            | Polycarbonate  |
| Form Factors Supported              | Mounting slots enable permanent placement of inverter on any horizontal surface (see manual for additional mounting information) |
| <b>ENVIRONMENTAL</b>                |  |
| Relative Humidity                   | 0-95% non-condensing   |
| <b>WARRANTY</b>                     |  |
| Product Warranty Period (Worldwide) | 1-year limited warranty  |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>