

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







REVISIONS DESCRIPTION REV. ECO. NO DATE 07/16/2010 2146 **INITIAL RELEASE** $2.429\pm.012[61.70\pm0.30]$ $.248 \pm .012 [6.30 \pm 0.30]$.100±.008[2.54±0.20] $.189\pm.008[4.80\pm0.20]$ $.039\pm.008[1.00\pm0.20]$.006 [0.16] 2X .142[3.60] POINT OF CONTACT(REF.) $.197\pm.004[5.00\pm0.10]$.094±.004[2.40±0.10] .118±.008[3.00±0.20] .248±.008[6.30±0.20] **NOTES:** 1. INSULATOR MATERIAL: PBT. 2. CONTACT MATERIAL: BRASS 3. PLATING: GOLD FLASH OVERALL. 4. UL FLAMMABILITY RATING: 94V-0. 5. DIELECTRIC WITHSTANDING VOLTAGE: 650V AC. 6. CURRENT RATING: 3 AMPS PER CONTACT. UNLESS OTHERWISE SPECIFIED: **ESULLINS** 7. CONTACT RESISTANCE: 30 MILLI OHMS MAX. DIMENSIONS ARE IN INCHES[MM] TOLERANCES: DRAWN 7/16/2010 LH THE INFORMATION HEREIN CONTAINS 8. INSULATION RESISTANCE: 1000 MEGA OHMS. ANGULAR: ± 30 PROPIETARY INFORMATION OF .XX=± .012 [.30] .XXX=± .008 [.20] .XXXX=± .004 [.10] SULLINS ELECTRONICS AND IS NOT TO BE REPRODUCED, USED OR DISCLOSED TO OTHERS FOR ANY MINI SHUNT, .100" CC, OPEN TOP 9. DOUBLE TUNING FORK TYPE CONTACT, ACCOMMODATES .025"[0.64mm] SQ PINS. PART NUMBER PURPOSE EXCEPT AS SPECIFICALLY .100"[2.54mm] PITCH LOW-PROFILE MINI TYPE. AUTHORIZED IN WRITING BY AN OFFICER OF SULLINS ELECTRONICS. QPC02SXHN-M290RC INTERPRET DIMENSIONS AND GEOMETRIC 10. OPERATING TEMPERATURE: -40° TO +85°C SIZE DWG. NO. REV TOLERANCING PER: ASME Y14.5M-2009 Α 11511 Rohs Compliant 11. MODIFICATION: CONTINUITY TYPE. SCALE: 16:1 SHEET 1 OF 1 6