



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



RAM[®] 6000 Cellular RTUs

Sixnet Networking Series



▶▶▶ Cellular Automation

Red Lion's Sixnet series RAM 6000 industrial cellular RTUs with 4G LTE provide a rugged, reliable solution for monitoring and controlling remote assets and processes in extreme conditions.

RAM 6000 RTUs seamlessly connect Modbus or DNP3 enabled SCADA equipment with master station or control center servers utilizing secure cellular 4G LTE or 3G wireless networks. A built-in I/O concentrator allows the RAM 6000 to collect local sensor data and optimize the cellular bandwidth by optionally reporting only on an exception. Ideal for deployment in industrial M2M networks such as oil and gas, water/wastewater, utility, transportation and mining applications, our industrial cellular RTUs provide a reliable network extension to remote locations. The end result helps customers save wiring time, space and cost by combining separate functions into one cellular device.



APPLICATIONS

- > Oil & Gas
- > Water/Wastewater
- > Utility
- > Transportation
- > Mining

PRODUCT HIGHLIGHTS

- > High-performance 4G LTE cellular connectivity
- > Natively supports Modbus and DNP3 protocols
- > Multiple communication ports
- > Routing capabilities provide secure, reliable communication

FEATURES & BENEFITS

- > Multiple Communication Ports
 - One RS232 serial port, and up to five Ethernet ports provide seamless connectivity to remote devices
- > Rugged, High-Performance Design
 - Reliable operation in rugged environments
 - -40° to 75°C operating temperature*
- > Modbus and DNP3 Support
 - Easily communicates with SCADA equipment with native protocols
- > Out-Of Band Management (OOBM)
 - Secure remote CLI access via RS232 port
 - Pre-loaded with many console port configurations
- > Secure Ethernet Connectivity
 - Routing capabilities for reliable communication
 - Stateful firewall, SSL, GRE and VPN services and packet inspection reduce the risk of unwanted access
- > Easy Configuration Options
 - Streamlined web-browser interface

industrial
networking



RAM 6000 Specifications

WIRELESS INTERFACE

AT&T LTE with fall back to HSPA+
 Bell Mobility LTE with fall back to HSPA+
 Generic LTE with fall back to HSPA+
 Manitoba LTE with fall back to HSPA+
 Rogers LTE with fall back to HSPA+
 Sprint EVDO Rev. A with fall back to 1xRTT
 TELUS LTE with fall back to HSPA+
 Verizon LTE with fall back to EVDO
 Dual-band CDMA2000 EVDO Rev. A
 (backward compatible with 1xRTT)
 GSM/HSPA+ (backward compatible with EDGE)

PROGRAMMABLE PLATFORM

Software Development Kit (SDK)
 C/C++/Perl

PROTOCOL GATEWAY

I/O controller
 Modbus RTU/TCP/ASCII
 DNP3 – slave

SYSTEM PERFORMANCE

32-bit ARM9 400 MHz CPU
 512 MB NAND
 128 MB RAM

TUNNELING

IPsec, GRE, OpenVPN

IP

NAT, port forwarding, dynamic DNS, DHCP
 Stateful inspection firewall, IP transparency

ETHERNET INTERFACE (10/100 AUTO-SENSING)

1x or 5x RJ45
 WAN capability on 5th port

SERIAL INTERFACE

1x RS232 serial DB9 115200bps

USB INTERFACE

1x USB 2.0 device mini

INPUTS & OUTPUTS

1x digital/analog inputs
 1x digital output (open-collector)

POWER INPUT

Range: 8-30 VDC (12 or 24 VDC nominal)
 Standby: 1.4W - 3.3W (typical)
 Transmitting:
 6401: 2.0W – 5.0W
 6421: 3.4W – 6.4W
 660x: 2.0W – 2.9W
 6621: 3.6W – 4.5W
 680x: 2.6W – 5.0W
 6821: 4.2W – 6.6W
 670x: 2.6W – 6.9W
 6721: 4.3W – 8.7W
 Heat dissipation: 30 BTU/hour max

MECHANICAL

RAM-6x0x
 Dimensions: 120 x 96 x 32 mm (4.7" x 3.77" x 1.25")
 Weight: 453g (1 lb)
 RAM-6x21
 Dimensions: 120 x 96 x 51 mm (4.7" x 3.77" x 2.0")
 Weight: 500g (1.1 lbs)

ENVIRONMENTAL

Operating temperature: -40° to +75°C*
 Shock: IEC60068-2-27
 Vibration: IEC60068-2-6
 Humidity: 5 to 95% non-condensing

CERTIFICATION


EMI/EMC:
 Emissions: FCC, Part 15 and Industry Canada, ICES-003; Class A;
 EN55022, IEC61000-6-4
 Immunity: IEC61000-6-2 (EN61000-4-2,3,4,5,6,8)
 Hazardous locations: Class I, Div. 2, Groups A, B, C, D, ISA 12.12.01
 Electrical safety: UL508/CSA22.2/14 (CUL); IEC61010-1
 Carrier specific approvals
 RoHS compliant

WARRANTY

3 years on design and manufacturing defects

* See Hardware Manual for thermal considerations.

DIMENSIONS in inches (mm)



RAM 6000 Specifications

ORDER GUIDE

PART NUMBER	PRODUCT LINE	SERIAL RS232	ETHERNET 10/100	CELLULAR	POWER CONNECTOR	SUPPORTED CARRIERS	
RAM-6600-(Carrier Code)	RAM	1	1	3G/CDMA	Molex end connector cable	(SP) Sprint; (VZ) Verizon	
RAM-6600-(Carrier Code)-AC	RAM	1	1	3G/CDMA	AC adapter		
RAM-6600-(Carrier Code)-MX	RAM	1	1	3G/CDMA	AC adapter/Molex end connector		
RAM-6601-(Carrier Code)	RAM	1	1	3G/CDMA	DC powered		
RAM-6601-(Carrier Code)-AC	RAM	1	1	3G/CDMA	AC adapter		
RAM-6601EB-(Carrier Code)	RAM	1	1	3G/CDMA	PoE (Power Over Ethernet)		
RAM-6621-(Carrier Code)	RAM	1	5	3G/CDMA	DC powered		
RAM-6621-(Carrier Code)-AC	RAM	1	5	3G/CDMA	AC adapter		
RAM-6700-(Carrier Code)	RAM	1	1	4G LTE	Molex end connector cable		(AT) AT&T; (BM) Bell Mobility; (GE) Generic*; (MTS) Manitoba; (RO) Rogers; (TE) TELUS; (VZ) Verizon
RAM-6700-(Carrier Code)-AC	RAM	1	1	4G LTE	AC adapter		
RAM-6700-(Carrier Code)-MX	RAM	1	1	4G LTE	AC adapter/Molex end connector		
RAM-6701-(Carrier Code)	RAM	1	1	4G LTE	DC powered		
RAM-6701-(Carrier Code)	RAM	1	1	4G LTE	AC adapter		
RAM-6701EB-(Carrier Code)	RAM	1	1	4G LTE	PoE (Power Over Ethernet)		
RAM-6721-(Carrier Code)	RAM	1	5	4G LTE	DC powered		
RAM-6721-(Carrier Code)-AC	RAM	1	5	4G LTE	AC adapter		
RAM-6800-(Carrier Code)	RAM	1	1	3G/GSM	Molex end connector cable	(AT) AT&T; (BM) Bell Mobility; (GE) Generic*; (MTS) Manitoba; (RO) Rogers; (TE) TELUS	
RAM-6800-(Carrier Code)-AC	RAM	1	1	3G/GSM	AC adapter		
RAM-6800-(Carrier Code)-MX	RAM	1	1	3G/GSM	AC adapter/Molex end connector		
RAM-6801-(Carrier Code)	RAM	1	1	3G/GSM	DC powered		
RAM-6801-(Carrier Code)-AC	RAM	1	1	3G/GSM	AC adapter		
RAM-6801EB-(Carrier Code)	RAM	1	1	3G/GSM	PoE (Power Over Ethernet)		
RAM-6821-(Carrier Code)	RAM	1	5	3G/GSM	DC powered		
RAM-6821-(Carrier Code)-AC	RAM	1	5	3G/GSM	AC adapter		

* See Band/Frequency table for compatibility

FREQUENCY SPECIFICATIONS

PART NUMBER	PRODUCT LINE
RAM-66XX-SP/VZ	EVDO: 800/1900 MHz CDMA: 800/1900 MHz LTE: Bands 1, 4, 17; Frequencies 700/2100MHz, AWS (1700/2100) MHz
RAM-67XX-AT/BM/GE/MTS/RO/TE	HSPA: Bands 1, 2, 5, 6; Frequencies 800/850/1900/2100 MHz GSM: 850/900MHz
RAM-67XX-VZ	LTE: Band 13; Frequency 700 MHz WCDMA: 850/900/1900/2100 MHz
RAM-68XX-AT/BM/GE/MTS/RO/TE	HSPA: Bands 1, 2, 5, 6, 8; Frequencies 800/850/900/1900/2100 MHz GSM: 850/900/1800/1900 MHz



www.redlion.net

Connect. Monitor. Control.

Americas
sales@redlion.net

Asia-Pacific
asia@redlion.net

**Europe
Middle East
Africa**
europe@redlion.net

+1 (717) 767-6511

As the global experts in communication, monitoring and control for industrial automation and networking, Red Lion has been delivering innovative solutions for over forty years. Our award-winning technology enables companies worldwide to gain real-time data visibility that drives productivity. Product brands include Red Lion, N-Tron and Sixnet. With headquarters in York, Pennsylvania, the company has offices across the Americas, Asia-Pacific and Europe. For more information, please visit www.redlion.net. Red Lion is a Spectris company.

ADLD0197 102814 © 2014 Red Lion Controls