imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



JACKS AND PLUGS

Subminiature Power Jacks

Switchcraft introduces a new series of sub-miniature power jacks. These sub-miniature power jacks feature ultra-compact housings and pin diameters as small as 0.65mm. Available in PC mount and true surface mount, with other options including open frame and shielded versions. All SMT versions come on tape and reel. Contact Switchcraft for exact reel dimensions.

Features and Benefits

- SMT mounting
- Tape and reel packaging
- Wide variety of circuits

Applications

- Computer
- Video Cameras
- Personal/Portable Audio Devices
- Multimedia

Specifications

Material

Housing: Black nylon Sleeve, ring, and tip terminals: Tin, silver-plated Shunt terminal: Brass, sliver-plated

Electrical

Current Rating: 3A Contact Resistance: <50 mohms Insulation Resistance: 100 mohms (min.) Dielectric Withstanding Voltage: 250VAC@ 1 minute

Mechanical

Lifecycles: 5,000 Operating Temperature: -25 to +85 C

Ordering Information

Part Number Description

RAPC742PC mount, 1mm pinRASM742TRSMT mount, 1mm pinRAPC732OFOpen frame, PC mount, 1.3mm pinRAPC742OFOpen frame, PC mount, 1.3mm pinRAPC752PC mount, 0.65mm pinRAPC752SShielded, PC mount, 0.65mm pinRASM752TRSMT mount, 0.65mm pinRASM752STRShielded, SMT mount, 0.65mm pin



PRODUCT Bulletin **547**

RAPC732OF

RAPC742

RASM752STR

RASM742TR

RASM752TR