mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



				REV.	DESCRIPTION	DATE	
				A A	NEW DRAWING	4/11/2006	
					tle corrected from right angle to vertical	5/11/2009	
4.00 [0.157] 13.00 [0.512] 11.50 [0.453]		F	- 19.50 [0.768]	0.394]	3.50 [0.138] - 1.40 [0.055] - 1.80 [0.071] - 3.30 [0.130] - 0.213]		
5.40 [0.213]			COLOR INDEX		TOLERANCE: ±0.3mm UNLESS OTHERWISE SPECIFIED	RoHS	
		-	PART NO.	COLOR		_	
		-	RCJ-051	Black			
	ĹĬ	-	RCJ-052	Red	- 🛞 CUI	INC	
└── 1.30X2.50			RCJ-052	White	20050 SW 112th Ave.		
PCB LAYOUT			RCJ-053	Yellow			
FRONT VIEW					Tualatin, OR 97062 Phone: 503-612-2300		
		Ļ	RCJ-055	Blue	800-275-4899	9	
			RCJ-056	Green	Fax: 503-612-23	383	
SPECIFICATIONS:			RCJ-057	Orange	Website: www.cui		
SPECIFICATIONS:	CONTACT RESISTANCE: 30m OHMS MAX				TITLE: RCJ JACK, VERTICAL, PCB MOUNT		
CONTACT RESISTANC				PLATING		B	
CONTACT RESISTANC	NCE: 100M OHMS MIN: 500V DC		ΜΔΙΕΡΙΔΙ				
CONTACT RESISTANC INSULATION RESISTAN VOLTAGE WITHSTANE	NCE: 100M OHMS MIN: 500V DC D: 500V AC R.M.S. FOR 1 MINUTE		MATERIAL		PART NO.	UNITS:	
CONTACT RESISTANC	NCE: 100M OHMS MIN: 500V DC D: 500V AC R.M.S. FOR 1 MINUTE	EARTH TERMINAL (1)	Brass	Nickel	RCJ-05X	MM [INCHES]	
CONTACT RESISTANC INSULATION RESISTAN VOLTAGE WITHSTAND LIFE: 5,000 CYCLES	NCE: 100M OHMS MIN: 500V DC D: 500V AC R.M.S. FOR 1 MINUTE	EARTH TERMINAL (1) PIN (2) HOUSING			PART NO. RCJ-05X DRAWN BY: ZRJ APPROVED BY:	MM [INCHES]	