



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



RD200 Refrigerant Leak Detector



Extech's Refrigerant Leak Detector is easy to use and is ideal for detecting leaks from air-conditioning units and cooling systems that use all standard refrigerants. The multi-colored LED light bar indicates the level of refrigerant detected by the RD200. Features a field replaceable heated diode sensor and Low/High sensitivity range selection for accurate leak detection. The 16" (406mm) flexible gooseneck provides easy access in difficult to reach locations.



Features

- Detects all standard refrigerants using a heated diode sensor (SF6, HFC, CFC, HCFC refrigerants, halogen gas, ethylene, tetrafluoroethylene, trichloroethylene, and most other compounds containing halogen)
- User-selectable sensitivity level:
 - Low - 1.05oz (30g) per year
 - High - 0.2oz (6g) per year
- Multi-colored LED light bar indicates the level of refrigerant leakage detected
- 19.8" (50.2cm) flexible gooseneck retains its shape and provides easy access in difficult to reach locations
- Audible and Visual alert
- Low battery indicator
- Convenient field replaceable sensor (RD200-S)
- Leak Test Bottle included for a quick and easy self test on meter performance
- Dimensions:
 - Meter - 7.3x2.8x1.4" (185x72x35mm)
 - Sensor with Gooseneck - 20.5" (520mm) long,
 - Probe Diameter - 0.32" (8mm)
 - Weight: 12oz (340g)
- Complete with sensor (installed), leak test bottle, 9V battery, and protective hard carrying case



Convenient rugged metal carrying case is included for added protection during storage and transportation of the meter.

Ordering

RD200..... Refrigerant Leak Detector
RD200-S..... Replacement Refrigerant Leak Sensor for RD200



RD200 UPC Code: 793950513033