

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China









## Programmable Relay I/O Card

MODEL NUMBER: RELAYIOCARD



### Description

Tripp Lite's RELAYIOCARD allows users to communicate UPS status and events via six configurable contact closure outputs. Installs in select expansion slot-equipped SmartOnline and select SmartPro UPS systems\*. Enables monitoring of UPS conditions and events. Provides input signal relay contact to perform remote UPS system shutdown or battery tests.

\*NOTE: SmartPro UPS systems including SMART1050SLT, SMART1500SLT, SMART2200RMXL2U, SMX1050SLT, SMART3000SLT, SMART2200SLT, SMART2200NAFTA, SMART2600RM2U, SMART3000RM2U, SMART1500CRMXL, SMART750XLa, SMX2200XLRT2U, and SMX3000XLRT2UA. Supported SmartPro systems must run UPS protocol 3008 or above. Works with most Tripp Lite Smart Online series models except the following; SU3000RTXL2U, SUINT3000RTXL2U, SUINT1000LCD2U, SUINT1500LCD2U, SUINT2200LCD2U, SUINT3000LCD2U, and SU3000LCD2UHV models.

#### **Features**

- Makes select Tripp Lite SmartPro or SmartOnline UPS capable of providing contact closure output communications
- 6 relay output contacts are configurable for normal open or normal close signaling of UPS conditions
- Configurable UPS conditions and events for each output relay contact
- Configurable input signal relay contact to shutdown UPS or test battery

## **Specifications**

OVERVIEW	
UPC Code	037332146410
Accessories Type	Relay I/O Card

### **Highlights**

- Programmable, internal contact closure management accessory card
- Six configurable relay output contacts
- Configurable input signal contact

## **Package Includes**

- RELAYIOCARD
- Configuration cable
- Faceplates
- Owner's Manual





Power Management Type	Network Interfaces	
OUTPUT		
Output Connector Type	Six configurable output relays; Screw-down terminal interface support 16-22 AWG wire sizes	
PHYSICAL		
Shipping Dimensions (hwd / in.)	6.000 x 1.750 x 6.200	
Shipping Dimensions (hwd / cm)	15.24 x 4.44 x 15.75	
Shipping Weight (lbs.)	0.6000	
Shipping Weight (kg)	0.27	
COMMUNICATIONS		
Communications Interface	Contact closure	
WARRANTY		
Product Warranty Period (Worldwide)	2-year limited warranty	

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>