



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



RI-03 Series Dry Reed Switch



RI-03 Series


Micro dry-reed switch hermetically sealed in a gas-filled envelope. Single-pole, single-throw (SPST) type, having normally open contacts, and containing two magnetically actuated reeds.

The switch is of the double-ended type and may be actuated by an electromagnet, a permanent magnet or a combination of both. The device is intended for use in sensors, relays, pulse counters or similar devices.

RI-03 Series Features

- Ideal for general purpose reed relays and sensors.
- Contact layers: ruthenium on gold
- Superior glass-to-metal seal and blade alignment
- RoHS Compliant

Dimensions for RI-03 Series



All Dimension in inches (mm) nominal

General data for all models RI-03

AT-Customization / Preformed Leads

Besides the standard models, customized products can also be supplied offering the following options:

- Operate and release ranges to customer specification
- Cropped and/or preformed leads

Coils

All characteristics are measured using the Philips Standard Coil. For definitions of the Philips Standard Coil, refer to "Application Notes" in the *Reed Switch Technical & Application Information* Section of this catalog.

Life expectancy and reliability

The life expectancy data given below are valid for a coil energized at 1.25 times the published maximum operate value for each type in the RI-03 series.

No load conditions (operating frequency: 100Hz)

Life expectancy: min. 10^8 operations with a failure rate of less than 10^{-9} with a confidence level of 90%.

End of life criteria:

Contact resistance > 1Ω after 2 ms

Release time > 2 ms (latching or contact sticking).

Loaded conditions (resistive load: 12 V; 4 mA; operating frequency: 170Hz)

Life expectancy: min. 10^6 operations with a failure rate of less than 10^{-8} with a confidence level of 90%.

End of life criteria:

Contact resistance > 2Ω after 4 ms

Release time > 0.7 ms (latching or contact sticking).

Switching different loads involves different life expectancy and reliability data. Further information is available on request.

Mechanical Data

Contact arrangement is normally open; lead finish is tinned; net mass is approximately 190mg; and can be mounted in any position.

Shock

The switches are tested in accordance with "IEC 68-2-27", test Ea (peak acceleration 150 G, half sinewave; duration 11 ms). Such a shock will not cause an open switch (no magnetic field present) to close, nor a switch kept closed by an 80 AT coil to open.

RI-03 Series Dry Reed Switch

Technical Specifications

| Parameters | Test Conditions | Units | RI-03AAA | RI-03AA | RI-03A | RI-03B |
|--|-------------------|-------|-----------------|-----------------|-----------------|-----------------|
| Operating Characteristics | | | | | | |
| Operate Range | | AT | 6-16 | 14-23 | 18-32 | 28-52 |
| Release Range | | AT | 3-15.5 | 6-21 | 7-27 | 10-36 |
| Operate Time - including Bounce (typ.) | | ms | 0.1 | 0.25 | 0.25 | 0.25 |
| Bounce Time (typ.) | | ms | 0.05 | 0.15 | 0.15 | 0.15 |
| Release Time (max) | | ms | 70 | 30 | 30 | 30 |
| Resonant Frequency (typ.) | | Hz | 5500 | 5500 | 5500 | 5500 |
| Electrical Characteristics | | | | | | |
| Switched Power (max) | | W | 5 | 10 | 10 | 10 |
| Switched Voltage DC (max) | | V | 160 | 200 | 200 | 200 |
| Switched Voltage AC, RMS value (max) | | V | 110 | 140 | 140 | 140 |
| Switched Current DC (max) | | mA | 250 | 500 | 500 | 500 |
| Switched Current AC, RMS value (max) | | mA | 250 | 500 | 500 | 500 |
| Carry Current DC (max) | | A | 1 | 1.5 | 2.5 | 2.5 |
| Breakdown Voltage (min) | | V | 200 | 250 | 300 | 350 |
| Contact Resistance (initial max.) | | mΩ | 120 | 120 | 120 | 120 |
| Contact Resistance (initial typ.) | | mΩ | 70 | 70 | 70 | 70 |
| Contact Capacitance (max) | without test coil | pF | 0.3 | 0.3 | 0.25 | 0.25 |
| Insulation Resistance (min) | RH ≤ 45% | MΩ | 10 ⁶ | 10 ⁶ | 10 ⁶ | 10 ⁶ |

Vibration

The switches are tested in accordance with “IEC 68-2-6”, test Fc (acceleration 10G; below cross-over-frequency 57 to 62 Hz; amplitude 0.75 mm; frequency range 10 to 2000 Hz; duration 90 minutes.) Such a vibration will not cause an open switch (no magnetic field present) to close, nor a switch kept closed by an 80 AT coil to open.

Mechanical Strength

The robustness of the terminations is tested in accordance with “IEC 68-2-21”, test Ua1 (load 40 N).

Operating and Storage Temperature

Operating ambient temperature; min: -55°C; max: +125°C. Storage temperature; min: -55°C; max: +125°C. Note: Temperature excursions up to 150°C may be permissible. For more information contact your nearest Comus Group sales office.

Soldering

The switch can withstand soldering heat in accordance with “IEC 68-2-20”, test Tb, method 1B: solder bath at 350 ± 10°C for 3.5 ± 0.5 s. Solderability is tested in accordance with “IEC 68-2-20” test Ta, method 3: solder globule temperature 235°C; ageing 1b: 4 hours steam.

Welding

The leads can be welded.

Mounting

The leads should not be bent closer than 1 mm to the glass-to-metal seals. Stress on the seals should be avoided. Care must be taken to prevent stray magnetic fields from influencing the operating and measuring conditions.

* As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.

RI-03 Series Dry Reed Switch



Comus International
454 Allwood Road
Clifton, New Jersey 07012
U.S.A

Tel: (1)973 - 777 - 6900
Fax: (1)973 - 777 - 8405
email: info@comus-intl.com
Website: <http://www.comus-intl.com>



Comus Relays & Sensors
37 Thurber Boulevard, Suite 102
Smithfield, Rhode Island 02917
U.S.A

Tel: (1)401 - 830 - 2100
email: sales@comusrelay.com
Website: <http://www.comusrelay.com>



Comus Europe Ltd
Unit 7, Rice Bridge Industrial Estate
Thorpe - Le - Soken
Essex, England
CO160HL

Tel: +44 (0)1255 862236
Fax: +44 (0)1255 862014
email: sales@comuseurope.co.uk
Website: <http://www.comuseurope.co.uk>



Comus Belgium BVBA
Overhaamlaan 40
B-3700 Tongeren
Belgium

Tel: +33 (0)12 390400
Fax: +33 (0)12 235754
email: info@comus.be
Website: <http://www.comus.be>



Comus Technology BV
Jan Campertstraat 11
6416 SG Heerlen
The Netherlands

Tel: +31(0)45 5439345
Fax: +31(0)45 5427216
email: info@comus-intl.com
Website: <http://www.dry-reeds.com>



Computer Components, Inc.
18-B Kripes Road.
P.O. Box 1378
East Granby, Connecticut 06026
U.S.A

Tel: (1)800 - 864 - 2815
email: info@relays-unlimited.com
Website: <http://www.relays-unlimited.com>



Comus Electronics and Technologies
India Private Limited
2nd Floor, No.31/33, Anjugam Nagar
2nd Street, Ashok Nagar, Jaferkhanpet
Chennai 600083
Tamil Nadu, India
Tel:+(91)-(44)-42023510
Fax:+(91)-(44)-22628198
email: info@comus-intl.com
Website: <http://www.comusindia.com>



Switching Technologies Gunther
B-9, B-10, & C-1
Special Economic Zone (MEPZ)
Kaddaperi, Tambaran
Chennai 600045
India

TAKE A LOOK AT OUR VARIETY OF PRODUCTS

