imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



	A , B , C ,	D E F F REVISIONS
		SYM ZONE ECN, ERN NO. DATE APPRD.
		B PROPOSAL MAY 12,05 L.CHAN C CHNAGE 11.81 TO 11.43 PER ACTUAL PART OCT29/12 L.CHAN
1		6.35 [.250] 1. MATERIALS:
	FRONT_VIEW	PLASTIC HOUSING: ENGINEERING THERMOPLASTIC FLAMMABILITY RATING UL 94V-0 COLOR: BLACK
2		CONTACTS: PHOSPHOR BRONZE PLATING: REFER TO PART NUMBER FOR GOLD 2 THICKNESS ON MATING SURFACES. 50 μ " [1.27 MICRONS] MIN. NICKEL UNDERPLATE 100 μ " [2.54 MICRONS] MIN. MATTE TIN OR GOLD FLASH ON CONTACT TAILS.
	1.90 [.075]	2. <u>MECHANICAL</u> :
3	ITYP. .63 [.025] TYP. .27 [.050] 03.25±0.05] 0.05] [ø.128±.002] 0.128±.002] HOLES 2 REQ'D 0.35 [.250]	MATING FORCE: 5.0 LBS MAX. 3. <u>ELECTRICAL</u> : CONTACT RESISTANCE: 40 MILLIOHMS MAXIMUM INSULATION RESISTANCE: 500 MEGOHMS MINIMUM CURRENT RATING: 1.5 AMPS VOLTAGE RATING: 1.25 VOLTS AC 4. <u>ENVIRONMENTAL</u> : STORAGE TEMPERATURE: -20°C to 85°C PACKAGING METHOD: TRAY PACKAGING
		PART_NUMBER: RJE08-188-0X10
	<u>RECOMMENDED P.C.B. LAYOUT</u> (COMPONENT SIDE OF BOARD)	$ \begin{array}{rcl} & \underline{\text{GOLD PLATING:}} \\ 1 &= 6 \mu^{"} \\ 2 &= 15 \mu^{"} \\ 3 &= 30 \mu^{"} \\ 4 &= 50 \mu^{"} \end{array} $
4		DRAWN PAULW Date of the observation DESIGNED Amphenol Canada Corp. CHECKED CHIGOW 05/12/05 I. E. APPRD. TITLE Q. A. APPRD. MODULAR JACK, TOP ENTRY, B POSITION, 8 CONTACTS, WITHOUT FLANGE, UNSHIELDED, - ROHS COMPLIANT
	THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM AMPHENOL CANADA CORP.	ENG. REL. NO. DWG DRAWING NO. P-RJE08-188-0X10 REV. REF. DIMENSIONS ARE IN CODE ID. NO. P-RJE08-188-0X10 C INCHES [mm] 03554 SCALE WT SURF SHEET 1 OF 1
	A B C	D E F