imall

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







No hassle warranty

NO HASSL

No waiting.

No shipping charges.

Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

RLD-1 Refrigerant Leak Detector

State of the art technology assuring precise, unambiguous readings, the RLD-1 makes leak finding across a wide variety of refrigerants easy and quick

- Precisely pinpoints a place of the leaks of the refrigerant in air-conditioning systems
- Sensor detects halogenated refrigerants such as R-134a, R-404A, R-407C, R-410A, R-22, Freon, etc.
- Suction pump provides instant response and quick sensor clearing, which speeds up the leak detection process
- Cutting edge accuracy with microprocessor controlled semiconductor gas sensor and advanced digital signal processing
- Clear leak indication with audio and tri-color visual LED display
- High-Medium-Low leak sensitivity selector
- Low battery indication
- Carrying case included
- 15.5" (40 CM) flexible stainless probe
- Reference Leak source included
- Ambient concentration reset
- Long-life, DC brushless fan
- Automatic zero and background compensation





RLD-1 Refrigerant Leak Detector

Data Sheet

Specifications

Detectable Gases	R-134a, R-404A, R-407C, R-410A, R-22 etc
Sensitivity	
R-22, 134a	H - 3g/year / M - 15g/year / L - 30g/year
R-404A, 407C, 410A	H - 4g/year / M - 20g/year / L - 40g/year
Alarm Method	Buzzer, Tricolor LED bar Indicator
Power Usage	2 C size (3V DC) Alkaline Batteries
Snake Tube Length	40cm (15.5")
Dimension / Weight	222 x 66 x 51 mm (8.7 x 2.6 x 2.0 in) (approximately 418g / 0.9 lb)
Accessories	Alkaline batteries (2C size) X 2 pcs, User manual, Leak check bottle, Carry case, AC Adapter
Battery Life	Approximately 16 hours normal use
Auto Power Off	10 minutes
Disable Auto Power Off	Press and Hold "Hi" button then power on the meter
Warm-Up Time	Approximately 45 seconds
Operating Temp. & Humidity	0 °C to 40 °C (32°F to 104°F), < 80% RH
Storage Temp. & Humidity	-10 °C to 60 °C (14°F to 140°F), < 70% RH
Altitude	< 2000M (6500′)

Amprobe® Test Tools

website: www.Amprobe.com email: info@amprobe.com Everett, WA 98203 Tel: 877-AMPROBE

Amprobe® Test Tools Europe

In den Engematten 14 79286 Glottertal, Germany Tel.: +49 (0) 7684 8009 - 0

©2009 Amprobe Test Tools. All rights reserved. 7/2009 3520393 Rev A