



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Suited for Advanced Users

Bridge Nylon by Taulman 3D

3 mm , 1lb reel

Taulman's "Bridge" high strength Nylon co-polymer bridges the strength of Nylon 645 and the ease of printing of ABS/PLA. Items printed in Bridge Nylon filament are stronger and more resilient than parts printed in more common materials.

PRODUCT ALERT (1)

Print Surface Recommendation:

Bridge is a nylon filament material, therefore applying a glue stick (such as Elmer's® brand) directly to the print surface before starting your LulzBot is strongly recommended

Works with: LulzBot Mini, LulzBot TAZ 6, LulzBot TAZ 5, LulzBot TAZ 1-4, LulzBot TAZ/Mini Aerostruder, LulzBot TAZ Dual Extruder, LulzBot TAZ FlexyDually, LulzBot Hexagon, LulzBot TAZ 6 Hexagon, LulzBot TAZ 5 Hexagon, LulzBot TAZ 1-4 Budaschnozzle, LulzBot Budaschnozzle

Features

Since Bridge prints cleanly and easily you can print complex models that are ready to be used. The combination of strength, reduced shrinkage, and ease in printing allows you to go from 3D model to 3D printed part ready to be installed. Bridge Nylon filament adheres well to the bed when treated with a PVA glue solution (water & PVA (Polyvinyl Acetate) glue) or a PVA glue stick. Bridge Nylon warps less than Nylon 618, 645 but slightly more than ABS, and prints well at 235°C. Like other Taulman nylons, Bridge can be dyed using Rit® brand dye to achieve custom color profiles.

Parts & Specifications

Filament Specifications

Filament Diameter: 3 mm (0.12 inches)

Amount of Filament: 1 lb (0.45 kg)

Filament color may vary

Printing Specifications

Special Tool Head Requirements: LulzBot Hexagon Hot End recommended

Hot End Temperature Range: 230°C - 240°C

Print Surface: PEI film recommended

Print Surface Temperature: 100°C

Packaging Information

Bridge filament ships vacuum sealed and mounted on a reel.

Storage Specifications

Store your filament in an air tight container. The use of desiccant is encouraged as nylon filament will absorb moisture from the air.