



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





Suited for Intermediate Users

colorFabb_HT by colorFabb

3 mm , 700g reel

colorFabb_HT is sturdy and ready for professional-grade applications. Engineered by colorFabb and Eastman Chemical Company, this Eastman Amphora™ co-polyester combines high temperature resistance and toughness for durable 3D printed objects.

PRODUCT ALERT (1)

Print Surface Recommendation:

colorFabb_HT adheres well to our PEI print surface. We strongly recommend applying PVA glue to directly on the print surface using a glue stick (such as Elmer's® brand) before printing to ensure easy part removal.

Works with: LulzBot Mini, LulzBot TAZ 6, LulzBot TAZ 5, LulzBot TAZ/Mini
Aerostruder

Colors



Black



Clear



White

- Features

colorFabb_HT is the strongest Eastman Amphora™-based co-polyester filament available and is able to withstand temperatures up to 100°C (212°F) when 3D printed. Like other Amphora-based premium 3D printing filaments, colorFabb_HT 3D prints with little-to-no odor and is styrene-free for warp-free and dimensionally stable parts. This makes colorFabb_HT perfect for interlocking, dimensionally stable 3D printed objects.

- Parts & Specifications

Filament Specifications

Filament Diameter: 3 mm (0.12 inches)

Amount of Filament: 700 g (1.54 lbs)

Filament color may vary

Printing Specifications

Special Tool Head Recommendation: LulzBot Hexagon Hot End recommended

Hot End Temperature: 275°C

Print Surface: PEI print surface recommended

Print Surface Temperature: 100°C

To make removing 3D printed objects easier, we strongly recommend applying a glue stick (such as Elmer's® brand) to the print surface prior to powering on your LulzBot 3D printer.

Maintain the print surface by powering off your LulzBot and cleaning the glue stick residue with a soft cloth and water.

Packaging Information

Sold in a sealed air-tight pouch, this filament is loaded onto a reel.