



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us


Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



Core **RM12/I**



Effective parameters			
	Parameter	Value	Unit
$\Sigma(I/A)$	core factor (C1)	0.388	mm ⁻¹
Ve	effective volume	8340	mm ³
Le	effective length	56.6	mm
Ae	effective area	146	mm ²
Amin	minimum area	125	mm ²
m	RM12/I	≈ 46	g/set

Dimensions for product: RM12/I

	Nom	Tol +	Tol -	Max	Min	Unit
A	29.80	0.00	1.10	29.80	28.70	mm
B	5.00			5.00	5.00	mm
C	16.10	0.00	0.50	16.10	15.60	mm
D2	25.00	1.00	0.00	26.00	25.00	mm
D3	12.80	0.00	0.40	12.80	12.40	mm
E					12.90	mm
G	37.40	0.00	1.30	37.40	36.10	mm
H1	24.50	0.10	0.10	24.60	24.40	mm
H2	16.80	0.60	0.00	17.40	16.80	mm
H3	21.60	0.25	0.25	21.85	21.35	mm

Inductance factor

Material	Value	Tol +	Tol -	Unit
3C94	5600	25%	25%	nH/turns ²
3C95	6790	25%	25%	nH/turns ²
3C96	5050	25%	25%	nH/turns ²
3C97	6790	25%	25%	nH/turns ²
3F36	3600	25%	25%	nH/turns ²
3F4	2600	25%	25%	nH/turns ²

Power loss: 3C94

Measuring conditions			Max	Unit
100 kHz	200 mT	100 °C	4.200	W/set

Core **RM12/I**

Power loss: 3C95				
Measuring conditions			Max	Unit
100 kHz	200 mT	100 °C	4.000	W/set
100 kHz	200 mT	25 °C	4.300	W/set
Power loss: 3C96				
Measuring conditions			Max	Unit
100 kHz	200 mT	100 °C	3.800	W/set
400 kHz	50 mT	100 °C	1.500	W/set
Power loss: 3C97				
Measuring conditions			Max	Unit
100 kHz	200 mT	60 °C	4.200	W/set
100 kHz	200 mT	120 °C	4.000	W/set
100 kHz	200 mT	140 °C	5.000	W/set
Power loss: 3F36				
Measuring conditions			Max	Unit
500 kHz	50 mT	100 °C	1.300	W/set
500 kHz	100 mT	100 °C	9.600	W/set
Power loss: 3F4				
Measuring conditions			Max	Unit
1000 kHz	30 mT	100 °C	2.500	W/set
3000 kHz	10 mT	100 °C	4.200	W/set

Bsat					
Measuring conditions			Material	Min	Unit
25 kHz	250 A/m	100 °C	3C94	320	mT
25 kHz	250 A/m	100 °C	3C95	330	mT
25 kHz	250 A/m	100 °C	3C96	340	mT
25 kHz	250 A/m	100 °C	3C97	330	mT
25 kHz	250 A/m	100 °C	3F36	340	mT
25 kHz	250 A/m	100 °C	3F4	330	mT

Accessories		
Ordering name	Description	Ordering code
CLI/P-RM12/I	Clip, with ground pin	432202134911
CPV-RM12/I-1S-12PD	Coil former, termoplastic, vertical	432202134112
CPV-RM12/I-1S-12PD-TZ	Coil former, termoplastic, vertical	432202106671
CSV-RM12-1S-11P-T	Coil former, termoset, vertical	432202104551
CSV-RM12-1S-12P-TZ	Coil former, termoset, vertical	432202106621