



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



## RNGFAP12DMMKLCB

Article Number: 904-00799

RapidNet Fiber Adapter Panel 12 DUP, MM, LC Brown 1/pkg



Download spec sheet

### Base Data

|                              |  |
|------------------------------|--|
| <b>Local Order Number</b>    | RNGFAP12DMMKLCB  |
| <b>Type</b>                  | RNGFAP   |
| <b>Color</b>                 | Brown (BN)   |
| <b>Features and Benefits</b> | <ul style="list-style-type: none"> <li>• Ideal for installations with limited access or restricted space.</li> <li>• Available in in 6 or 12 hole configuration.</li> <li>• Allows ruggedized fan-outs to be presented in RapidNet Panels.</li> <li>• Fits into a standard RapidNet Panel.</li> <li>• Supports a maximum of 1152 fibers in 1U of space.</li> </ul>   |
| <b>Product Description</b>   | The RapidNet Fiber Adapter Panel is designed to allow the RapidNet solution to be used in areas with limited access or restricted space, where a RapidNet Cassette cannot be used. Panels are pre-loaded with adapters, which allow ruggedized fan-outs to be presented in RapidNet panels - offering a maximum of 288 fibers in a single adapter, or 1152 fibers in 1U of space.  |
| <b>Technical Description</b> | The RapidNet Fiber Adapter Panel is supplied in a 12 or 6 hole configuration. Panels are customized with a choice of MTP, SC or LC adapters. Panels can be used in any RapidNet panel, but are recommended for use with the RapidNet Distribution Chassis or Rear Cable Management Panel, to provide rear cable management and protection for the fan-out cable. All fiber adapters and connectors comply with the latest published version of IEC874-14, ensuring interoperability. |
| <b>Short Description</b>     | RapidNet Fiber Adapter Panel 12 DUP, MM, LC Brown 1/pkg  |

### Product Dimensions

|                            |                       |
|----------------------------|-----------------------|
| <b>Length L (Imperial)</b> | 2.1 "                 |
| <b>Length L (Metric)</b>   | 53.75 mm              |
| <b>Ferrule Type</b>        | Zirconia Ceramic (ZC) |
| <b>Fiber Count</b>         | 24                    |
| <b>Width W (Imperial)</b>  | 4.0 "                 |
| <b>Width W (Metric)</b>    | 102.7 mm              |
| <b>Height H (Imperial)</b> | 1.1 "                 |
| <b>Height H (Metric)</b>   | 27.8 mm               |

### Logistics and Packaging

|                                  |         |
|----------------------------------|---------|
| <b>Quantity Per</b>              | box     |
| <b>Package Quantity (Metric)</b> | 1       |
| <b>Weight (imperial)</b>         | 4 oz    |
| <b>Weight (Metric)</b>           | 113.4 g |

### Material and Specifications

|                 |         |
|-----------------|---------|
| <b>Material</b> | Plastic |
|-----------------|---------|

