



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



SO5NF STD

UPC : N/A

Model : S8213

Qty. : 1

New Product



Package:

One polybag one piece

Description:

.20g with torque 2.8kg-cm (2.8V) 3.2kg-cm (6V); wire: 18cm Metal Gear Servo.

Feature:

- Futaba, JR, Sanwa and Hitec compatible.

Important Notes:

- Specify the connector type when you purchase the servo.
- Refer to the figure when installing the servo accessories.
- For engine powered airplanes and boats, rubber must be used to reduce vibration.
- Please choose correct model for your application.
- Torque over-loaded will damage the servo's mechanism.
- Keep the servo clean and away from dust, corrosive gas and humid air.

Specification

(Specifications are subjected to change without notice.)

Wire (cm)	Size (MM)					Weight		4.8V			6V		
								Speed	Torque		Speed	Torque	
	A	B	C	D	E	g	oz	sec/60°	kg-cm	oz-in	sec/60°	kg-cm	oz-in
18	2.8.8	13.8	30.2			20		0.20	2.8		0.18	3.2	

