

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







Panasonic RP-SDP

P Series

SD Memory Card, Industrial MLC Model

■ Product Outline

P series are SDHC memory cards adopting built-in industrial MLC type NAND flash memory and is suitable for industrial applications. They are adequate for the applications such as automotive use, security camera, factory automation, broadcast equipment, handy terminal etc. They are formatted complying with SD card specification.

■ **Product Specification** (specifications and appearances may be changed without notice.)

Appearance Part Number RP-SDP04G RP-SDP08G RP-SDP16G RP-SDP16	Trouble Specification (specifications and a		4GB	8GB	16GB
Capacity Available user data area capacity*1) 3,955,195,904 byte 7,998,504,960 byte 16,194,174,976 byte Compliant Specification SD Physical Specification Ver. 3.01 SD speed class □ CLASS (€) UHS speed grade not supported Backside mark Control Code D0BC Read/Write Performance (up to) Read (High Speed) (High Speed) (High Speed) Write 12MB/s (High Speed) (High Speed) (High Speed) Absolute Maximum Ratings Supply Voltage Input Voltage Output Voltage Output Voltage Output Current Min: -0.3V Max: VDD+0.3V Max: VDD+0.3V Max: VDD+0.3V Max: VDD+0.3V Max: VDD+0.3V Max: VDD+0.3V	Appearance		₹ € € 4GB	8GB MLC	16GB MLC
Capacity	Part Number		RP-SDP04G	RP-SDP08G	RP-SDP16G
Compliant Specification SD speed class UHS speed grade Speed mode Backside mark Control Code Read/Write Performance (up to) Write Absolute Maximum Ratings Raings SD speed class UHS speed class □ CLASS € DOBC Read/Write Backside mark Control Code DOBC Supply Voltage Input Voltage Output Voltage Output Current CLASS € CLASS € CLASS € DOBC High Speed, Default Speed High Speed, Default Speed (High Speed) (High Speed) (High Speed) (High Speed) (High Speed) (High Speed) (High Speed) CHICASS € Mini -0.3V Max: VDD+0.3V Mini: -0.3V Max: VDD+0.3V Mini: -0.3V Max: VDD+0.3V Output Current Mini: -24mA Max: 24mA	Capacity		3,955,195,904 byte	7,998,504,960 byte	16,194,174,976 byte
Compilant Specifiction		•	Ver. 3.01		
Backside mark Control Code Read/Write Performance (up to) Absolute Maximum Ratings With Speed grade Speed mode Control Code DOBC DOBC 22MB/s (High Speed) (High Speed) (High Spee		SD speed class	CLASS@		
Backside mark Control Code D0BC Read/Write Performance (up to) Read (High Speed)		UHS speed grade	not supported		
Read/Write Performance (up to) Read 22MB/s (High Speed) 22MB/s (High Speed) 22MB/s (High Speed) Absolute Maximum Ratings Supply Voltage Input Voltage Output Voltage Output Current Min: -0.3V Max: VDD+0.3V		Speed mode	High Speed, Default Speed		
Read/Write Performance (up to) Read (High Speed)	Backside mark	Control Code	DOBC		
(up to) Write 12MB/s (High Speed) 12MB/s (High Speed) 12MB/s (High Speed) Absolute Maximum Ratings Supply Voltage Input Voltage Output Voltage Output Voltage Output Current Min: -0.3V Max: VDD+0.3V Max: VD	Performance	Read			
Absolute Maximum Ratings Input Voltage Output Voltage Min: -0.3V Max: VDD+0.3V Min: -0.3V Max: VDD+0.3V Min: -0.4mA Max: 24mA		Write			
Maximum Ratings Output Voltage Min: -0.3V Max: VDD+0.3V Output Voltage Min: -0.3V Max: VDD+0.3V Min: -24mA Max: 24mA	Maximum	Supply Voltage			
Ratings Output Voltage Min: -0.3V Max: VDD+0.3V Output Current Min: -24mA Max: 24mA					
Output Current Min - 24mA Max 24mA					
10 1 M 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1 0 1					
Operating Temperature -40 degree C to 85 degree C	Environmental Specification	}	-40 degree C to 85 degree C -40 degree C to 85 degree C		
		}	-40 degree C to 85 degree C 5 % to 95 %		
			1000 G		
Mating Cycles 10,000 cycles					

^{*1)} Free area capacity after formatted


Absolute maximum ratings are the values of limitation, which do not damage the card. Those values do not define the operational range.

Products comply with EU RoHS directives.

Specification Number: PSD1162DG00

Panasonic RP-SDP

■Laser Mark on the Back-side (example; 4GB)



"0000" Control Code (Defined as product parts combination)
"00YM0000000" Serial Number
Y Last digit of Manufacture year
M Manufacture month (January->A, February->B,)
"4GB" Card Capacity
"P" Series name
"MADE IN JAPAN" Country of origin

■ System Reliability

- a. Powerful error detect and corrective function
- b. Static wear leveling
- c. Data recovery at power failure in writing
- d. Automatic refresh function
- e. Bad block management

■ Notice and Caution

If you think about the usage for which special quality or reliability of the products is needed and failure or malfunction of the products may directly threaten life or injury for the special usage (aeronautic or cosmic usage, military usage, combustion machine, life support applications or safety applications), please counsel with our contacts in advance.

Write frequency and storage temperature will affect data retention time. Please make a backup for important data.

■ Warranty

If the product cannot be used because of failure which is determined as defect in design or in production of the product, it is replaced by same product or equivalent one within 12 months from the delivery date of product.

Specification Number: PSD1162DG00