



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts,Customers Priority,Honest Operation,and Considerate Service",our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China






KC Series

microSD Memory Card, Industrial MLC Model

■ **Product Outline**

KC series are the SDHC memory cards adopting built-in industrial type MLC NAND flash memory, and suitable for industrial applications. They are adequate for applications such as automotive use, security camera, factory automation, broadcast equipment, etc. They are formatted complying SD card specification.

■ **Product Specification** (specifications and appearances may be changed without notice.)

		4GB	8GB	16GB
Appearance				
Part Number		RP-SMKC04DA1	RP-SMKC08DA1	RP-SMKC16DA1
Capacity	Available user data area capacity *1)	3,955,195,904 byte	7,998,504,960 byte	16,198,369,280 byte
Compliant Specification	SD Physical Specification	Ver. 3.01		
	SD speed class	CLASS [®]		
	UHS speed grade	UHS speed grade 0		
	Speed mode	Default Speed mode, High Speed mode, UHS-I (SDR12, SDR25, DDR50, SDR50)		
Backside mark	Control Code	---		
Read/Write Performance (up to)	Read	45MB/s (DDR50, SDR50)	45MB/s (DDR50, SDR50)	45MB/s (DDR50, SDR50)
	Write	12MB/s (High Speed, DDR50, SDR50)	12MB/s (High Speed, DDR50, SDR50)	20MB/s (High Speed, DDR50, SDR50)
Absolute Maximum Ratings	Supply Voltage	Min : -0.3 V ; Max : +4.6 V		
	Input Voltage	Min : -0.3 V ; Max : VDD +0.3 V		
	Output Voltage	Min : -0.3 V ; Max : VDD +0.3 V		
	Output Current	Min : -24 mA ; Max : +24 mA		
Environmental Specification	Operating Temperature	-40 degree C to +85 degree C		
	Storage Temperature	-40 degree C to +85 degree C		
	Humidity	5 % RH to 95 % RH		
	Vibration	15 Gp-p		
	Shock	1,000 G		
	Mating Cycles	10,000 cycles		

*1) Free user area capacity after formatted.

Absolute Maximum Ratings are the values of limitation, which do not damage the card. So those values do not define the operational range.

Products comply with EU RoHS directives.

■ Marking Specification (example; 4GB)



- “4GB” Card Capacity
- “U” Internal control code
- “MADE IN JAPAN” Country of origin
- “00YM0000000” Serial Number
 - Y Last digit of Manufacture year
 - M Manufacture month (January->A, February->B,)

■ System Reliability

- a. Powerful error detect and corrective function
- b. Static wear leveling
- c. Data recovery at power failure in writing
- d. Automatic refresh function
- e. Bad block management

■ Notice and Caution

If you think about the usage for which special quality or reliability of the products is needed and failure or malfunction of the products may directly threaten life or injury for the special usage (aeronautic or cosmic usage, military usage, combustion machine, life support applications or safety applications), please counsel with our contacts in advance.

Write frequency and storage temperature will affect data retention time. Please make a backup for important data.

■ Warranty

If the product cannot be used because of failure which is determined as defect in design or in production of the product, it is replaced by same product or equivalent one within 12 months from the delivery date of product.