

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## RP6V2

#### **Robotic Vehicle**

#### **RP6V2 Capabilities:**

Cruise around autonomously

Avoid obstacles

Follow light sources

Measure light intensity

**Detect collisions** 

Detect blocked engines

Detect low battery

Measure and control rotational speed of motors via highresolution encoders

Move given distance

Rotate specific angles

Measure driven distance


Move in geometric paths: circles, polygons, and others

Exchange data with other robots or devices

Operate as remote control car (RC5)

Transfer sensor data to PC via USB

Expand via I<sup>2</sup>C bus



#### Features:

- ATMEGA32 8-bit RISC microcontroller with 8 MIPS and 8MHz clock
- Delivered fully assembled (no soldering needed)
- CD with software, 138 page manual, and many extras
- AVR-GCC and RobotLoader open source software for use with Windows and Linux
- Programmable in C
- Receives IR codes in RC5 format
- USB Interface for easy programming and communication
- Module I<sup>2</sup>C bus expansion system
- Expansion boards may be stacked as needed
- Sample C programs and huge C function library
- Powerful tank drive train can drive up steep ramps and over obstacles
- Large payload capacity
- Light, collision, speed and IR-obstacle sensors integrated
- Two 7.2V DC motors
- 625 CPR encoder resolution for precise speed regulation
- Six PCB expansion areas

#### Overview:

The RP6V2 is an economical autonomous mobile robot system which provides an introduction to the fascinating world of robotics. It is designed for beginners as well as experienced electronics and software developers.

Programmable in C, the RP6V2 has many possibilities for expansion as your programming skills grow.

The RP6V2 is ideal for educational curriculum at universities, trade schools, high schools and of course hobby users.

With an extensive manual, lots of example programs, and a huge C function library, programming is easy and you can instantly start experimenting with your robot. All library and example programs are open source (GNU GPL)!

RobotLoader Screen Shot





# RP6V2

RP6V2 comes with the following items:

RP6V2 vehicle

CD

10-pin connector

USB connector cable

USB programmer interface

Available Accessories

RP6V2-M32

RP6v2-WIFI

RP6V2-EXP

RP6V2-DSP

## Specifications

Model RP6V2	
Processor memory	32KB Flash ROM 2 KB SRAM 1 KB EEPROM
USB upload rate	500kBaud
Expansion system	Two-wire I <sup>2</sup> C bus 400 kBit/s transfers 127 devices
Encoder resolution	625 CPR
Max speed of vehicle	25 cm/s
Traverse obstacles	ca. 2 cm height
Negotiate ramps	30% steepness 40% with modifications
Bumper sensors	2 in front
ACS (Anti-Collision-System)	IR receiver and two IR diodes for left and right
Status LEDs	6 (4 may be appropriated)
Light sensors	2
ADC (Analog to Digital Converter)	2 (may be used as I/0)
Motor drivers	2 optimized MOSFET H- Bridges
Ground clearance	10 mm
Power supply connectors	2 x 5V and 1 x 7.2V
Voltage regulator	5V
Operating time	3-6 hours
Power supply	6 AA rechargeable batteries (not included)
Current consumption	500 mA
Dimensions (L x W x H)	172 x 128 x 50 mm
Technical data subject to change without notice	

# Training & Support Manual on CD

Chapter 1: Introduction
Expansion and technical data
What the RP6 can do
Application suggestions

Chapter 2: The RP6 in Detail Control system Power supply Sensors Drive system Expansion system

Chapter 3: Hardware & Software Setup

Chapter 4: Programming the RP6
Configuring the Source Code Editor
Program upload to the RP6
Why C? And what's "GCC"?
C- Crash Course for Beginners
Makefiles
The RP6 function library
Example programs

Chapter 5: Experiment Board

Chapter 6: Closing Words

Appendix:

Troubleshooting
Encoder calibration
Connector pinouts
Recycling and safety instructions







globalspecialties.com