# mail

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832 Email & Skype: info@chipsmall.com Web: www.chipsmall.com Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







### **Combination Tachometer + IR Thermometer**

Photo/Contact Tachometer includes a non-contact IR Thermometer For non-contact surface temperature measurements

#### **Features:**

- Built-in IR thermometer with laser measures remote surface temperature on motors and rotating parts
- Wide Temperature range of -4 to 600°F (-20 to 315°C)
- Fixed 0.95 emissivity, 6:1 distance to target ratio
- Provides wide RPM (photo and contact) and Linear Surface Speed (contact) measurements
- Accurate to 0.05% with max resolution of 0.1rpm in either photo or contact mode
- Large 0.4" (5 digit) LCD display
- Non-contact Photo tachometer uses a Laser for greater measuring distance up to 6.5ft (2m)
- Contact tachometer for RPM and surface speed measurements
- Memory stores Min/Max/Last
- Characters on display reverse direction depending on mode
- Double molded housing
- Complete with tips/wheel, four 1.5V AA batteries, reflective tape, and carrying case



Non-contact model for use on machinery where high speed measurements are required



Accessory wheels enable tachometer to measure linear surface speeds



	•
Specifications	
Display counts	99,999 count LCD
Range (rpm)	Photo: 10 to 99,999/ Contact: 0.5 to 20,000
ft/min	0.2 to 6560 (Contact)
m/min	0.05 to 1999.9 (Contact)
Basic Accuracy	$\pm (0.05\%$ rdg+1 digit)
Max rpm Resolution	0.1rpm
Temperature (IR)	-4 to 600°F (-20 to 315°C)
Dimensions	8.5 x 2.6 x 1.5" (216 x 66 x 38mm)
Weight	10.6oz (300g)

#### **Ordering Information:**

CE

#### www.extech.com