



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



RPS8-750ATX-XE



Main Features

- Full range AC input 100-240V
- Support PMBus v1.2
- Common safety for CUL / CB / CCC / CE / FCC / TUV / BSMI
- Support OTP, OVP and OCP circuit protection
- 80 Plus Gold Available

Product Spec

Product	RPS8-750ATX-XE
Product Description	FSP AC 100-240V 750W W/PFC 2U(1+1)Redundant
Application	(1+1)R
Manufacturer	FSP Technology
Subcategory	Mini Redundant
Form Factor	2U
Output Power	750W
Output	+3.3V @ 24A;+5V @ 30A;+12V @ 60.9A;-12V@ 0.5A;+5Vsb @ 4A
Efficiency	80%
80 Plus Certified	80 Plus Gold
Main Connector	ATX (20 + 4pin)
Input Voltage Range	100 - 240V
Input Current	10A
Input Frequency	47 - 63Hz
Input Current Type	AC to DC
PFC Function	W/PFC
Dimensions (D×W×H)(mm)	200×150×84
Storage Temp	-40 - 70°C
Storage Humidity	95% RH
Operating Temperature	0 - 60°C
MTBF	100K hours at 25°C
FAN Speed Control	YES
Power Switch Function	Yes
Safety & EMC	Class B
Safety Standard	CUL / CB / CCC / CE / FCC / TUV / BSMI
RoHS Status	Yes
EOL	Q4 / 2020
Replacement Model	TBA
Maximum Power	

700W and above