

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







0.866 [21.0]

0.945 [24.0]

Panel Cutout 1.240 [31.5] X 1.126 [28.6] 0.547 [13.9] **RSC1-Series RSC2-Series** 1.071 [27.2] | 0.476 [12.1] 0.657 [16.7] **RSC3-Series** 1.071 [27.2] 0.547 [13.9] RSC4-Series 1.126 [28.6] | 0.476 [12.1] **Actuator Options**

0 U


Bi-Color



1.102 [28.0] 0.079 [2.0] 0.307 [7.8]

0.732 [18.5]

Illumination Options



Terminal Options





0 4.8mm Tab

6.3mm Tab (Small Hole)



Solder



Body

Color

0

0.473 [12.0]

0.280 [7.1]

Series	Terminal	Function	Rating
Curved Actuators: RSC1 - 28.6 x 13.9 Cutout RSC2 - 27.2 x 12.1 Cutout	1 - 4.8mm Tab 4 - 6.3mm Tab (Small Hole)	1 - Off-On (*) 3 - On-On 4 - Off-(On)	C - 15A 1 D - 20A 1

- 15A 125V 1 Black D - 20A 125V 2 - White 3 - Almond
 - 1 4.8mm Tab 1 Off-On (*) (4 6.3mm Tab 3 On-On (5mall Hole) 4 Off-(On) 5 Solder 5 On-Off-On (9 6.3mm Tab A- On-(Off) (1.arge Hole) 8 On-(On) (C Solder C On-Off-(On)
 - 4 Grey 9 Red (Low Clearance)
- Marking Actuator Marking Color Color

- Almond

- Grey - Orange

- Blue

- Green - Red

Bi-Color: A - Black / Red

0 - None 1 - Black 2 - White 0 - Full Illum. Black White

8 - Red

- Type 0 - None
- Style 1 - Full

Lens

- I/O Vert. ON/OFF/ON Vert. - ON/OFF Vert.
- 3 6V 4 12V 5 24V 1 - Red 2 - Amber 6 - 125V 7 - 250V 3 - Green ON/OFF Horiz I/O/II Horiz.

Lens

Color

0 - Clear

Lamp

Voltage

- I/O Horiz S - I/O/II Vert



For Illuminated Switches Only

FEATURES:

- · Excellent Quality and Reliability
- · 4 Bodies to Cover Many Popular Cutouts
- High Current Capacity
- · Illuminated and Bi-Color Actuators

SPECIFICATIONS: RATING: RATING OPTION D:

20A 125VAC [cURus] 16A 250VAC [cURus] 1/4HP 125VAC [UL] 3/4HP 250VAC [UL] 16(4)A 250V~ 1E4 T125 [European] 20(8)A 250V~ 1E4 T125 [European] 10(2)A 250V~ 5E4 T125 [European]

RATING OPTION C: 15A 125VAC [cURus] 10(4)A 250V~ 1E4 T85 [European]

TEMPERATURE: -20°C to 65°C [cURus] -20°C to 105°C [cURus] -20°C to 125°C [European]

ELECTRICAL LIFE: 10,000 Cycles CONTACT RESISTANCE: 20mΩ Max. at 1A 5VDC

Insulation Resistance: $100M\Omega$ Min. at 500VDCDIELECTRIC STRENGTH: 1,000VAC for 1 Minute

MATERIALS:

Bopy: Polyamide 6/6, UL94 V-2 Actuator: Polyamide 6/6, UL94 V-2 Polycarbonate, UL94 V-2 CONTACTS: Silver

TERMINALS: Silver Plated Copper



RSC341D1123



RSC241D2200

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE



RSC141D1021-116

EXAMPLE PART NUMBERS:

1P Off-On RSC141D1000-126 Black Body, Amber Illum. Actuator, 125V

RSC141D1100 1P Off-On Black Body/Actuator, No Marking

RSC141D1121 1P Off-On Black Body/Actuator, I/O Vert.

RSC141D2200 1P Off-On White Body/Actuator, No Marking



Flat Actuators

RSC3 - 27.2 x 13.9 Cutout

RSC4 - 28.6 x 12.1 Cutout

RSCF1 - 28.6 x 13.9 Cutout RSCF2 - 27.2 x 12.1 Cutout

RSCF3 - 27.2 x 13.9 Cutout

