

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







	PART NO.	"A" REF.	"B"±.016	INTERCHANGE
	RSDC-250	2.5 (63.5)	(±0.41) 1.5 (38.1)	WITH SCANBE 11633-1
	RSDC-300	3.0 (76.2)	2.0 (50.8)	11000 1
	RSDC-350	3.5 (88.9)	2.5 (63.5)	
	RSDC-400 RSDC-450	4.0 (101.6) 4.5 (114.3)	3.0 (76.2) 3.5 (88.9)	11633-2
	RSDC-500	5.0 (127.0)	4.0 (101.6)	11000 2
	RSDC-550 RSDC-600	5.5 (139.7) 6.0 (152.4)	4.5 (114.3)	
	RSDC-650	6.5 (164.1)	5.0 (127.0) 5.5 (139.7)	11633-3
	RSDC-700	7.0 (177.8)	6.0 (152.4)	
	RSDC-750 RSDC-800	7.5 (190.5) 8.0 (203.2)	6.5 (165.1) 7.0 (177.8)	11633-6
	1000 000	1 0.0 (200.2)	7.0 (177.0)	1 11000 0
•				
.31 (7.9)				
<u> </u>				
	"A"	_ 1	_ 1 1	- 075 (10)
.1/3 (4.4)]	——— A ——		_ -	- .075 (1.9)
<u> </u>			<u>*</u>	пі
		+	T 1	1 1 (1 7)
†	\oplus	.125	$(3.2) \rightarrow \forall \forall$.17 (4.3)
.50 (12.7)	ĺ			†
TYP.	——— "B" ——	-		
		. = a+ 00	17	
"B" \pm .005 (\pm 0.13) $-$ (4.47 $^{+0.08}_{-0.03}$)				
	′ 1	(4.4/_0.0	3)	
		 		
		1		
.180 + .003		.225+.00	3 1	
$(4.57^{+0.08}_{-0.03})^{-1}$	→ - →	(5.71+0.0	83)	
DE	COMMENDED MOUNTIN	C HOLFS		
RECOMMENDED MOUNTING HOLES PANEL THICKNESS: .047090 (1.2-2.3)				E ECN #831 SM R CHANGES 08.09.04
		,	FCOMPI	FTFLY REDRAWN SM
			-	"NO TAMPER JL
				AMP" ON PRINT 08.07.00
			C DIM	225 (5.7) RS S .255 (6.5) 01.25.93
NOTES:				Be
1. MATERIAL: NYLON 6/6 (RMS-48).				A WAS REF. 11.25.92
2. COLOR: NATURAL.				TRIC DIMS RS CORRECTED 08.17.92
			R E DE	SCRIPTION ENGR
TITLE: CNIAD INI CADD CI IIDE				DATE DWG IN
SNAP-IN CARD GUIDE			ノ <u> </u>	MM) NI T
TOLERANCES FILE # RSDC UNLESS NOTED MAT'L: SEE N		P.B. APP: 405-94 DT:	PART #	FINAL
.XX=±.010		RICHCO INC.		PRINT
FRAC=±1/64 ANG=±1*	ICO, INC.	OX 804238,CHICAGO,6	,0000	TABLE TABLE
	ı	(773) 539-4060)	$1 \cup \cap 1$