



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



RSF66P Series

Dual switch point series with M12 connection



- High & Low level switching
- PPS material
- Versions for Filling or Emptying Control
- M12 4 pin connection for quick connection to circuit
- WRAS and NSF Approved

Technical Specification (Common to both Single and Double Float versions)

Mechanical	Electrical	
Material	PPS	
Colour	Grey	
Temp. Range °C	-10 / +85	
°F	+14 / +185	
Minimum Liquid SG	0.85	
	Switching power VA max.	25
	Switching Voltage AC max	240
	Switching Voltage DC max	120
	Switching Current max A	0.6
	All electrical ratings are for resistive loads only.	

Standard Parts Single Float Versions	Upper switch Level	Lower switch Level	Total length
RSF66A25B75P	30mm	75mm	102mm
RSF66A25B100P	30mm	100mm	127mm
RSF66A25B125P	30mm	125mm	152mm
RSF66A25B150P	30mm	150mm	177mm
RSF66A25B175P	30mm	175mm	202mm

Dual Float Versions

RSF66A50A100P	Emptying Control	50mm	100mm	134mm
RSF66A50A150P	Emptying Control	50mm	150mm	184mm
RSF66B50B100P	Filling Control	50mm	100mm	127mm
RSF66B50B150P	Filling Control	50mm	150mm	177mm

Custom versions can be made for particular applications. Please contact Cynergy3 with your requirements.


The RSF66 float switch series is designed to offer a number of switching options to meet a variety of system requirements.

These are manufactured in PPS (Polyphenylene Sulphide), which is compatible with a wide range of liquids.

The single float types are generally used in systems with PLC control of processes.

The dual float versions can be used for controlling the filling or emptying of tanks via electromechanical relays.

Mechanical Dimensions



Cynergy3 Components Ltd.
7 Cobham Road
Ferndown Industrial Estate
Wimborne, Dorset BH21 7PE
Telephone +44 (0) 1202 897969

Email: sales@cynergy3.com

RSF66P 2017

ISO9001 CERTIFIED



Made in the UK

www.cynergy3.com