

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China










M12-Round-Plug Connector, Double-Ended Cordsets, According to IEC 61076-2-101

RST -RKT | RST-RKWT

3-, 4-, 5- and 8-Poles

Actuator/sensor cordset, double-ended, M12, 3-, 4-, 5- and 8-poles, male straight to female straight connector with self-locking thread and molded TPE, PUR, or PVC cable, IEC color code.


RST-RKT





Actuator/sensor cordset, double-ended, M12, 3-, 4-, 5- and 8-poles, male straight to female 90° connector with self-locking thread and molded TPE, PUR, or PVC cable, IEC color code.

RST-RKWT



Pin Assignments

3 poles 4 poles 5 poles (794) 5 poles (all others) 8 poles 4 poles 4 poles 5 poles (794) 5 poles (all others) 4 poles 5 poles (all others) 4 poles 5 poles (all others) 6 poles (all others) 7 poles (all others) 8 poles (all others) 7 poles (all others) 7 poles (all others) 8 poles (all others) 7 poles (all others) 8 poles (all others) 7 poles (all others) 8 poles (all others) 7 poles (all othe

Be Certain with Belden



M12-Round-Plug Connector, Double-Ended Cordsets, According to IEC 61076-2-101 RST-RKT | RST-RKWT

Technical Data

Environmental

Degree of protection Operating temperature range

PUR: -40°C (-40°F) / +80°C (176°F) PVC: -40°C (-40°F) / +90°C (194°F) TPE: -40°C (-40°F) / +90°C (194°F)

Mechanical

Housing / Molded body

PUR, yellow RST 8-RKT 8-627: PUR, black RST 8-RKWT 8-627: PUR, black

RST 8-RKWT 8-627: PUR, orange

Insert

PUR, Yellow RST 8-RKT 8-627: PUR, orange

IP 67 / NEMA 6P

Contacts Coupling nut

CuSn, gold over nickel-plated CuZn, nickel-plated FKM or Viton

O-ring (female only) **Electrical**

Current rating RST 8-RKT 8-XXX:

1.5A

4 A

Voltage rating

250 V 5-Pole: 60V

8-Pole: 30 V AC /36 V DC

Cable Specifications

Cable No.	Outer Jacket	Gauge	Jacket Color	OD				
602	PUR	18 AWG	Yellow	.230" (5.8 mm)				
Continuous flex rating and suitable for general C-track usage. 1 million cycles at minimum bend radius 10X cable diameter.								
610	PUR	22 AWG	Yellow	.190" (4.8 mm)				
612	PVC	22 AWG	Yellow	.210" (5.3 mm)				
627	PVC	24 AWG	Black	.232" (5.9 mm)				
632	PVC	22 AWG	Yellow	.190" (4.8 mm)				
633	PVC	22 AWG	Yellow	.190" (4.8 mm)				
637	TPE/PLTC	18 AWG	Yellow	.280" (7.1 mm)				
643	TPE/PLTC	22 AWG	Yellow	.246" (6.2 mm)				
644	PUR	22 AWG	Yellow	.210" (5.3 mm)				
645	PUR	18 AWG	Yellow	.220" (5.6 mm)				
679	PUR	22 AWG	Yellow	.190" (4.8 mm)				
713	TPE/PLTC	22 AWG	Yellow	.280" (7.1 mm)				
727	TPE/PLTC	22 AWG	Yellow	.335" (8.5 mm)				
731	TPE/PLTC	18 AWG	Yellow	.261" (6.6 mm)				
794	TPE/PLTC	18 AWG	Yellow	.304" (7.7 mm)				

Part Number		Dino	Outer Jacket	Standard Cable Lengths	Characteristics
		Pins			Characteristics
RST 3-RKT 4-3-731/M	RST 3-RKWT 4-3-731/M	3	TPE/PLTC	2 M / 5 M / 10 M	
RST 3-RKT 4-3-632/M	RST 3-RKWT 4-3-632/M		PVC	2 M / 5 M / 10 M	
RST 3-RKT 4-3-645/M	RST 3-RKWT 4-3-645/M		PUR	2 M / 5 M / 10 M	
RST 3-RKT 4-3-610/M	RST 3-RKWT 4-3-610/M		PUR	2 M / 5 M / 10 M	
RST 4-RKT 4-637/M	RST 4-RKWT 4-637/M	4	TPE/PLTC	1 M / 2 M / 3 M / 5 M / 6 M / 10 M	
RST 4-RKT 4-633/M	RST 4-RKWT 4-633/M		PVC	2 M / 5 M / 10 M	H H H
RST 4-RKT 4-643/M	RST 4-RKWT 4-643/M		TPE/PLTC	1 M / 2 M / 5 M / 10 M	
RST 4-RKT 4-602/M	RST 4-RKWT 4-602/M		PUR	1 M/2 M/3 M/4 M/5 M/6 M/10 M	
RST 4-RKT 4-679/M	RST 4-RKWT 4-679/M		PUR	2 M / 5 M / 10 M	
RST 5-RKT 5-612/M	RST 5-RKWT 5-612/M	5	PVC	2 M / 5 M / 10 M	
RST 5-RKT 5-644/M	RST 5-RKWT 5-644/M		PUR	2 M / 5 M / 10 M	
RST 5-RKT 5-713/M	RST 5-RKWT 5-713/M		TPE/PLTC	2 M / 5 M / 10 M	
RST 5-RKT 5-794/M	RST 5-RKWT 5-794/M		TPE/PLTC	2 M / 5 M / 10 M	
RST 8-RKT 8-627/M	RST 8-RKWT 8-627/M	8	PVC	2 M / 5 M / 10 M	
RST 8-RKT 8-727/M	RST 8-RKWT 8-727/M		TPE/PLTC	2 M / 5 M / 10 M	