



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!




Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



C O N F I G U R A T I O N		P A R T N U M B E R	
F e m a l e J a m n u t R e c e p t a c l e , 8 P i n , 16 A w g , S h e l l 12		RT07128SNH	
D I M E N S I O N S			
 <p>The technical drawing includes three views of the connector: a side view, a front view, and a panel cut out reference view. The side view shows dimensions of 33.0, 21.10, 19.30, 10.00, and 19.00. It labels the 11/16-24 UNEF thread, O-Ring, O-Ring Fixed In Position, Nut, Insert, Seal Gasket, and Shell. The front view shows a hexagonal shell with 8 pins labeled A through H, with dimensions of 31.8 and 31.8. The panel cut out reference view shows a circular cutout with dimensions of Ø 22.50 and 21.20.</p>			
T E C H N I C A L D A T A			
TEMPERATURE RANGE:	-40°C to + 105°C		
PRO T E C T I O N:	IP67 in m a t e d c o n d i t i o n a n d i n c o m b i n a t i o n w i t h s e a l e d b a c k s h e l l		
V O L T A G E R A T I N G:	250V		
H O U S I N G B O D Y:	Z i n c A l l o y , N i c k e l P l a t e d		
C O U P L I N G N U T:	-		
I N S E R T:	G l a s s - f i l l e d T h e r m o p l a s t i c U L 9 4 - V 0		
S E A L:	NBR		
C U R R E N T:	13A		
C O N T A C T S I Z E:	16Awg		
A P P R O V A L S:	U L E C B 2		