

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China








# MINIATURE TELEPHONE JACKS, RIGHT ANGLE, PC MOUNT





Right-angle miniature phone jacks provide low-profile packaging. Single and twin 3-conductor jacks provide plug-jack access to communication circuits for patching and/or testing. Tips and rings are shunted. These jacks mate with Switchcraft miniature TT® plugs and patch cords.

Jacks are designed for right-angle mounting on .062" (1.6 mm) maximum thickness PC boards. Snap-on covers in colors are available and can be installed or removed in the field without special tools. Covers and jacks may be ordered in different colors for color coded circuits.

# SPECIFICATIONS

### **ELECTRICAL**

Dielectric Withstanding Voltage: 500 V AC Contact Resistance: .020  $\Omega$  maximum (initial),

.030  $\Omega$  maximum (after life test).

Insulation Resistance:  $10^{10} \Omega$  at 500 V DC (initial).

## **MECHANICAL**

Shock: MIL-STD 202 Method 213. Vibration: MIL-STD 202 Method 201.

**Insertion Force:** 7 pounds maximum (31.14 N). **Withdrawal Force:** 1.5 pounds minimum (6.67 N).

Life: 10,000 cycles.

# **MATERIALS**

**Housing:** Thermoplastic UL 94V-0. **Springs:** Copper alloy, plated.

Contacts: Gold alloy (WEco #1) crossbar.

#### **ENVIRONMENTAL**


Temperature Limits: -55°C to +85°C

(non-operating).

Thermal Shock: MIL-STD 202 Method 107. Salt Spray: MIL-STD 202 Method 101. Humidity: MIL-STD 202 Method 106, less

steps 7A and 7B.

Still Comme = Comment of the only



# ORDERING INFORMATION

Jack Part No.	Cover Part No.	Color	Schem.	Cond.	Typical Mating Plug <sup>2</sup>	
RTT34B01	<b>♦</b> P286301	Red			TT-253	
RTT34B02	P286302	Black				
RTT34B04	<b>♦</b> P286304	Blue	\			
RTT34B05	P286305	White	XII	3		
♦RTT34B07	<b>♦</b> P286307	Orange				
♦RTT34B08	♦P286308	Yellow	1			

RTT8701	<b>♦</b> P286401	Red			TT-263
RTT8702	P286402	Black			
RTT8704	♦P286404	Blue	Twin	Twin	
RTT8705	P286405	White	XII	3	
♦RTT8707	♦P286407	Orange			
♦RTT8708	♦P286408	Yellow			

- 1. See schematic diagrams on pages 79 and 80.
- 2. See Mating Plugs Section.
- ♦ Special order only; contact Switchcraft for price and delivery.

### **ORDERING**

- 1. Order jacks and covers separately from table.
- 2. Covers can be ordered assembled on special order.
- 3. To order RTT jack with cover installed, add the letter C after RTT in part number. Special order only.
- To order RTT jack with Snap-in terminals, add the letter S to the end of the part number. Special order only.
- 5. For all special orders items, contact Switchcraft.

#### RTT JACK PART NUMBERING SYSTEM

Series	Cover Option		Circuitry		Jack Color	
RTT Right Angle TT Jack	Blank-	No Cover Standard	34B-	XII	01-	Red
	C-	Cover Supplied	87-	Two XII Circuits	02-	Black
					04-	Blue
					05-	White
					07-	Orange
					08-	Yellow