



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China



RTV Silicones

RTV Silicones by MOMENTIVE performance materials

2-Part Potting/Encapsulating Compound

RTV615



Technical Support
for RTV Silicones

 1-800-255-8886

M.G. Chemicals Disclaimer
for RTV Silicones >

[Locate Distributor >](#)

Quick Links

- [▶ MSDS](#)
- [▶ Catalyst options/MSDS](#)
- [▶ Primer options/MSDS](#)
- [▶ Specifications](#)
- [▶ Available Sizes](#)

Related products:

- [RTV103 Black](#)
- [RTV108 Translucent](#)
- [RTV109 Aluminum](#)

Resources


- [▶ Selection Guide >](#)
- [▶ One Part Chart !\[\]\(adb0331d22f78481623cc605df40612a_img.jpg\)](#)
- [▶ Two Part Chart !\[\]\(7e3a264c08e10137510d1aa76522412b_img.jpg\)](#)

Find by Application

- [General Purpose >](#)
- [Aerospace >](#)
- [Marine >](#)
- [High Performance Assembly >](#)
- [Electronics >](#)
- [Thermal Conductivity >](#)
- [High Temperature >](#)
- [Low Temperature >](#)



Google Search MG

RTV Number... 

ALL MG PRODUCTS ▾

Jump to Product Number

Product Number... 

[Accessories](#)

[Adhesives](#)

[Brushes](#)

[Cleaners / Degreasers](#)

[Contact Cleaners](#)

[Desoldering Braid](#)

[Dusters & Circuit Coolers](#)

[EMI / RFI Shielding](#)

[Epoxies](#)

[Flux and Flux Remover](#)

[Glass & Screen Cleaners](#)

[Isopropyl Alcohol](#)

[Lead Free Solder](#)

[Lubricants](#)

[Potting & Encapsulating](#)

[Protective Coatings](#)

[Pens](#)

[Prototyping Materials](#)

[RTV Silicones](#)

[Soldering/desoldering](#)

[Specialized Cleaners](#)

[Swabs](#)

[Thermal Management](#)

[Thermally Conductive](#)

[Adhesives](#)

[Wipes](#)

[▶ STOCKED ITEM](#)

[▶ BUY NOW](#)

Primary Characteristics

- ▶ **Optically Clear**
- ▶ **Easily pourable**
- ▶ **Addition cure**
- ▶ **Primer required**
- ▶ **FDA Approved**

Use for:

- ▶ Solar cell potting
- ▶ Optical instruments
- ▶ Applications requiring visual identification of potted assemblies
- ▶ Food applications

Excellent for potting solar cells for maximum light transmission and electronic assemblies where component identification is desirable. This two part silicone is supplied with a curing agent. [Primer](#) required. Cures at room temperature. Has low viscosity allowing easy flow in and around complex parts, providing excellent electrical insulation and shock resistance. Clarity permits visual inspection for easy identification and repair of encapsulated parts. Excellent retention of elastomeric properties at temperatures up to 204°C (400°F). Will cure in deep sections or enclosed assemblies without exotherm and with low shrinkage. Can be used in food contact applications where FDA 21 CFR 177.2600 regulations apply.

Available Sizes

Catalog Number	Sizes Available	Description
RTV615-1P	1 pint	1 lb kit
RTV615-1G	1 gallon	10 lbs. kit
RTV615-5G ▶ SPECIAL ORDER	5 gallon	44 lbs. kit
RTV615 requires a primer. Visit our primer guide for details.		

Specifications

Use	Adhesive Sealant
Special Feature	High tensile strength Optically Clear
Standards	FDA 21CFR 177.2600
Cross Reference	RTV615
Uncured Properties	
Consistency	Easily pourable
Color	Optical clear
Specific Gravity	1.05
Tack Free Time	4 hours
Cure Through Time	6 - 7 days @ 25°C 15 min @ 150°C
Useful Temp. Range	-60°C to 205°C (-75°F to 400°F)
Cured Properties - MECHANICAL	
Hardness	44 (Shore A)

Tensile Strength	6.37 MPa (920 psi)
Elongation	120%
Cured Properties - ELECTRICAL	
Volume Resistivity	1.8×10^{15} ohm · cm
Dielectric Strength	19.7 kV/mm
	500 V/mil
Dielectric Constant	2.7 @ 1000 Hz
Cured Properties - THERMAL	
Thermal Conductivity	0.19 W/m · °K
Brittle Point	-60°C (-75°F)
Thermal Expansion	27×10^{-5} (°C) ⁻¹
Other	
Viscosity (@ 25°C)	4,000 cps
Mix Ratio (by weight)	10 : 1
Pot Life	4 hours
Index of Refraction	1.406

[Return to top](#) ^