



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





S10 - VERSASENSE LIGHT SENSOR

PRODUCT DESCRIPTION

The VersaSense Light Sensor (**S10**) detects the level of ambient light in lumens.

VERSASENSE SENSORS

VersaSense Sensors are self-identifying sensors and actuators that connect to VersaSense Wireless Devices to provide plug-and-play sensing and control.

The VersaSense software automatically installs and configures all drivers, eliminating the cost and complexity of deploying an IoT network.

Note: only one peripheral of this type may be connected to a VersaSense Wireless Device.

APPLICATIONS

The light sensor supports environmental sensing. Applications include:

- ★ Workplace monitoring
- ★ Monitoring of animal enclosures
- ★ Smart lighting systems
- ★ Weather monitoring systems
- ★ Monitoring compliance with perishable goods storage

CORE COMPONENTS

The **S10** is based on the VEML6040 from Vishay®, for more information please visit:

[Vishay_VEML6040.pdf](#)

S10 CHARACTERISTICS

Characteristic	Value	Unit
Min/Max light intensity	0/16496	lx
Min/Max temperature	-40/85	°C
Accuracy light intensity	+/- 0.01	lx
Min/Max period between updates	10 / 86400	s
Avg current: period = 1hour	42	nA
Avg current: period = 60s	2.5	µA
Avg current: period = 10s	15	µA

Note: avg current values represent the current that this sensor draws from a VersaSense Wireless Device that is configured with the noted update period. This value excludes message transmission.

RELATED PRODUCTS

Item **S10** requires a VersaSense Wireless Device such as **Pxx** or **Lxx**. This item is compatible with all items in the VersaSense catalog:

versasense.com/files/VersaSense-Catalog.pdf

INFORMATION/SUPPORT

Web: www.versasense.com

Sales: sales@versasense.com

Help: support@versasense.com

Other: info@versasense.com

Post: VersaSense NV, Kapeldreef 60, 3001 Leuven, Belgium.