

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







S1D13748



S1D13748 WVGA LCD Controller

The S1D13748 is a low cost, low power WVGA LCD Controller providing TFT panel support for embedded products requiring up to WVGA resolution. Supporting up to three display layers, the S1D13748 provides the host processor with flexibility in handling multiple image sources. Its ability to receive high speed host writes, combined with its support for a wide variety of LCD panels, makes the S1D13748 an excellent choice for a multitude of LCD applications.

The S1D13748 includes a pixel doubling feature which allows easy migration to larger panel sizes using existing image data. The feature set includes independent resizing of PIP window image data using the bi-cubic scaler, scrolling control for each layer, and LCD output manipulation such as gamma control and optional dithering. This allows the host processor to provide image data, but off-loads the image processing requirement from the host.


The S1D13748 contains 1024 KB of embedded SRAM which is used to store image data for up to three layers which are combined to output the panel image. This feature set provides a low cost, low power single chip solution to meet the demands of embedded markets requiring up to WVGA resolution.

FEATURES

- Embedded 1024 KB SRAM display buffer
- Low operating voltage
- 16-bit indirect host interface
 - High speed host writes
 - Rectangular, rotated, and mirror host write modes
 - Input formats: YUV 4:2:2, 4:2:0 and RGB 5:6:5
- Support for TFT panels
- RGB interface: 9/12/16/18/24-bit

- Support for up to 3 display layers with overlay and alpha blending
 - Main layer image can be doubled in size
 - PIP1 layer can be resized from 8x to 1/8x
 - PIP2 layer can be resized from 8x to 1/8x
- Independent scrolling control for each layer
- LUT for gamma control of LCD output
- · Optional dithering of LCD output
- Internal PLL or digital clock input
- Software initiated power save mode
- PFBGA 121-pin or QFP20 144-pin packages

SYSTEM BLOCK DIAGRAM



S1D13748 Features

- 1024 KB SRAM
- Up to 3 display layers
- Overlay and alpha blending
- Display scrolling
- Gamma control of LCD output







S1D13748



DESCRIPTION

CPU Interface

- 16-bit Indirect host interface
- Supports high speed host writes
- Integrated host interface write controller supports: rectangular, rotated and mirror write modes

Input Data Format

- RGB: 5:6:5
- YUV 4:2:2, 4:2:0

Display Support

- Supports TFT panels
- 9/12/16/18/24-bit RGB interface

Miscellaneous

- Internal PLL or digital clock input (CLKI)
- Software initiated power save mode
- Hardware/software power save mode
- Input pin to enable/disable power save mode
- General purpose input/output pins
- COREVDD 1.5 volts IOVDD 1.80, 2.80, or 3.30 volts
- PFBGA 121-pin and QFP20 144-pin packages available

Display Memory

Embedded 1024 KB SRAM

Display Features

- Supports up to 3 layers with overlay and alpha blending functions
- Main layer features:
 - o Image can be stored as RGB 5:6:5
 - Pixel doubling which doubles the size of the display image (independent horizontal/vertical)
- PIP1 Layer features:
 - Image can be stored as RGB 5:6:5 or YUV 4:2:2
 - o Bi-cubic scaler can resize image from 8x 1/8x
 - Edge enhancement support
- PIP2 Layer features:
 - Image can be stored as RGB 5:6:5 or YUV 4:2:2
 - Bi-cubic scaler can resize image from 8x 1/8x
 - Panorama function allows variable vertical scaling
 - o Edge enhancement support
 - LUT for independent gamma control of PIP2 window
- Independent display scrolling for each layer (Main, PIP1, PIP2)
- LUT for gamma control of the LCD output
- Optional dithering for the LCD output

JAPAN SEIKO EPSON CORPORATION

IC Sales & Marketing Department 421-8 Hino, Hino-shi, Tokyo 191-8501, JAPAN

CHINA EPSON (CHINA) CO., LTD

4th Floor, Tower 1 of China Central Place, 81 Jianguo Road, Chaoyang District, Beijing 100025, CHINA

Phone: +86-10-8522-1199 FAX: +86-10-8522-1120

TAIWAN EPSON TAIWAN TECHNOLOGY & TRADING LTD.

14F, No. 7, Song Ren Road, Taipei 110, TAIWAN

Phone: +886-2-8786-6688 FAX: +886-2-8786-6660

AMERICA EPSON ELECTRONICS AMERICA, INC.

214 Devcon Drive, San Jose, CA 95112,

USA Phono: 11 8

Phone: +1-800-228-3964 FAX: +1-408-922-0238

CHINA SHANGHAI Branch

Room 01 & 04 17F, Greenland Center II, 562 Dong An Road, Shanghai 200032, CHINA

Phone: +86-21-5423-5577 FAX: +86-21-5423-4677

SINGAPORE EPSON SINGAPORE PTE., LTD.

1 HarbourFront Place,

#03-02 HarbourFront Tower One, SINGAPORE 098633 Phone: +65-6586-5500 FAX: +65-6271-3182

EUROPE EPSON EUROPE ELECTRONICS GmbH

Riesstrasse 15, 80992 Munich, GERMANY

Phone: +49-89-14005-0

FAX: +49-89-14005-110

CHINA SHENZHEN Branch

Room 804-805, 8th Floor, Tower 2, Ali Center, No.3331 Keyuan South RD (Shenzhen bay), Nanshan District, Shenzhen 518054. CHINA

Phone: +86-10-3299-0588 FAX: +86-10-3299-0560

......

KOREA SEIKO EPSON CORP.

19F, KLI 63 Bldg., 60 Yoido-dong,

Youngdeungpo-Ku, Seoul 150-763, KOREA



http://global.epson.com/products/semicon

NOTICE: Document code: X80A-C-001-02.1

No part of this material may be reproduced or duplicated in any form or by any means without the written permission of Seiko Epson. Seiko Epson reserves the right to make changes to this material without notice. Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products. Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party. When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations. You are requested not to use, to resell, to export and/or to otherwise dispose of the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military numbers.

All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective companies. ©Seiko Epson Corporation 2006, 2017. All rights reserved.