

Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from, Europe, America and south Asia, supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of "Quality Parts, Customers Priority, Honest Operation, and Considerate Service", our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip, ALPS, ROHM, Xilinx, Pulse, ON, Everlight and Freescale. Main products comprise IC, Modules, Potentiometer, IC Socket, Relay, Connector. Our parts cover such applications as commercial, industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



# Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China







## LOW ATTENUATION INTERCONNECT CABLE ASSEMBLY

LAI-290 Group

Frequency Range: DC-18 GHz

#### **ELECTRICALS**

Velocity of Propagation	S	85
RF Leakage Min. @ 18GHz	dR/ft	-100
Impedance	Nominal	50
Capacitance	pF/ft (pF/m)	24 (78.72)
Delay	nett (nem)	1.20 (3.94)
Breakdown Voltage	kV	>15
Phase Stability vs Flexure	deal(dea of bend per GHz)	<,0003

### MECHANICAL/ENVIRONMENTAL

Nominal Diameter	inches (cm)	.290 (.737)
Minimum Bend Radius	inches (cm)	1.6 (4.064)
Temperature	DEG.C	-65/+200
Weight	th.fti (g/m)	.09 (134)

#### MATERIALS AND FINISHES CONNECTOR


WATERIALS AND THISTIES COUNTED	1011
Body	Stainless steel
Nut	Stainless steel
Gasket	Silicone Rubber
Contact	BeCu / Gold plated
Insulator	PTFE

#### MATERIALS AND FINISHES CABLE

IMA LINEO AND I MIGHE THE	
Cable Jacket	FEP
Outer Shield	Silver Copper
Inter Conductor	Silver Copper
Dielectric	Micro-porous PTFE
Center Conductor	Silver Copper


#### CONNECTOR CODES FEMALE MALE CONNECTOR FREQ STYLE GHZ BULKHD ame RA 82 84 81 8MA 18 NI N2 N4 N TYPE 18 ET2 ET4 ET1 \*ETNC 18

## LA 290 CABLE ATTENUATION vs FREQUENCY



JACKET OPTIONS		
DESCRIPTION	CODE	
FEP JACKET	8F	
POLYURETHANE JACKET	BP	

\* EXTENDED FREQUENCY RANGE



HOW TO SPECIFY PART NUMBER

CONNECTOR

L 29

OPTION

CONNECTOR

STANDARD LENGTH (INCHES)

FOR EXAMPLE:

SMA STRAIGHT MALE TO SMA STRAIGHT FEMALE, FEP JACKET, 36 INCHES LONG. NOTE: USE LEADING ZEROS WHEN SPECIFYING LENGTH.

PART NUMBER 18:

81 L29 BF 83 036