



Chipsmall Limited consists of a professional team with an average of over 10 year of expertise in the distribution of electronic components. Based in Hongkong, we have already established firm and mutual-benefit business relationships with customers from,Europe,America and south Asia,supplying obsolete and hard-to-find components to meet their specific needs.

With the principle of “Quality Parts,Customers Priority,Honest Operation,and Considerate Service”,our business mainly focus on the distribution of electronic components. Line cards we deal with include Microchip,ALPS,ROHM,Xilinx,Pulse,ON,Everlight and Freescale. Main products comprise IC,Modules,Potentiometer,IC Socket,Relay,Connector.Our parts cover such applications as commercial,industrial, and automotives areas.

We are looking forward to setting up business relationship with you and hope to provide you with the best service and solution. Let us make a better world for our industry!



## Contact us

Tel: +86-755-8981 8866 Fax: +86-755-8427 6832

Email & Skype: info@chipsmall.com Web: www.chipsmall.com

Address: A1208, Overseas Decoration Building, #122 Zhenhua RD., Futian, Shenzhen, China





# TG-S606P

## Thermal Compound

Version 1.280318



### Thermal Compound

TG-S606P is an ultra high performance silicone grease. It has a thermal conductivity of 8 W/mK, superior wetting characteristics, resulting in a very low thermal resistance and excellent long term reliability.

### Features

- Good thermal conductivity
- Easy to assemble
- High stability
- Does not harden with time

### Applications

Electronic components: IC, CPU, MOS  
 LED, M/B, P/S, Heat Sink  
 LCD TV, Notebook PC, PC Telecom Device, Wireless Hub, etc.  
 DDR II Module, DVD Applications, Hand-set applications, etc.

### Properties

- ✓ REACH Compliant
- ✓ ROHS Compliant

Property	TG-S606P	Unit	Test Method
Colour	White	-	Visual
Thermal Conductivity	8.0	W/mK	ASTM D5470
Weight Loss	<0.5	%	ASTM E595
Density	2.3	g/cm <sup>3</sup>	ASTM D792
Working Temperature	-40 to 180	°C	-
Volume Resistance	>10 <sup>12</sup>	Ohm-cm	ASTM D257

### Standard Packaging

Size	Packaging	Weight (gr)
	Plastic Jar	300ml
	Pail	1 kg

### Storage

TG-S606P has a self-life of eighteen (18) months from the date of manufacture, as indicated by the lot number, when stored in the original, unopened container at, or below 25°C.

T-Global Technology Limited  
 1 & 2 Cosford Business Park, Central Park,  
 Lutterworth, Leicestershire LE17 4QU U.K.

Tel: +44 (0)1455 553 510  
 Email: sales@tglobaltechnology.com  
 Web: www.tglobaltechnology.com  
 Skype: tglobal.technology  
 VAT #: GB 116 662 714

NOTICE: The information contained herein is to the best of our knowledge true and accurate. However, since the varied conditions of potential use are beyond our control, all recommendations or suggestions are presented without guarantee or responsibility on our part and users should make their own test to determine the suitability of our products in any specific situation. This product is sold without warranty either expressed or implied, of fitness for a particular purpose or otherwise, except that this product shall be of standard quality, and except to the extent otherwise stated in T-Global Technology Europe and North America's invoice, quotation, or order acknowledgment. We disclaim any and all liabilities incurred in connection with the use of information contained herein, or otherwise. All risks of such are assumed by the user. Furthermore, nothing contained herein shall be construed as a recommendation to use any process or to manufacture or to use any product in conflict with existing or future patents covering any product or material or its use.